WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.	
1 LOCATION OF WATER WELL: County: FINNEY	Fraction 1/4 NW 1/4 SE 1/4 NW 1/4	Section Number Township No. Range Number 17 T 26 S R 33 □E ✓	
Street/Rural Address of Well Location	n; if unknown, distance & direction	Global Positioning System (GPS) information:	
from nearest town or intersection: If	at owner's address, check here .	Latitude:3779066 (in decimal degrees)	
GARDEN CITY- 12 M. S. TO TV		Longitude: 100, 95636 (in decimal degrees)	
3,735 FT. NORTH & 3,620 FT. WEST		Elevation:	
		Datum: WGS 84, NAD 83, NAD 27	
	ESTONE	Collection Method: X GPS unit (Make/Model: Garmin 62ST)	
and the commence of	5 S. SANDHILL ROAD	Digital Map/Photo, Topographic Map, Land Survey	
City, State, 211 Code . GARI	DEN CITY, KS. 67846	Est. Accuracy: $\square < 3 \text{ m}$, $\square 3-5 \text{ m}$, $\square 5-15 \text{ m}$, $\square >15 \text{ m}$	
3 LOCATE WELL			
WITH AN "X" IN 4 DEPTH O	F COMPLETED WELL 480		
SECTION BOX: Depth(s) Grow			
N WELL'S STA	N WELL'S STATIC WATER LEVEL. 237 ft. below land surface measured on mo/day/yr. 3-23-12 Pump test data: Well water was		
Pu	mp test data: Well water was	ft. after hours pumping gpm	
1 " 1 VY " " - IND		ft. after hours pumping gpm t., and ft.	
W	ER TO BE USED AS: Public wat		
Domostio	Feedlot Oil field water	er supply Dewatering Other (Specify below)	
SW SE	☐ Industrial ☐ Domestic-lay	vn & garden Monitoring well	
Was a chemic	cal/bacteriological sample submitted to	Department? Yes V No	
s If yes, r	no/day/yr sample was submitted	· — — — — — — — — — — — — — — — — — — —	
Water well di	sinfected? Yes No		
5 TYPE OF CASING USED: Steel PVC Other			
CASING JOINTS: Glued Clamped Welded Threaded			
Casing diameter 16 in to 290 ft., Diameter in to ft., Diameter in to ft.			
Casing height above land surface1	2 in., Weight 42.05	lbs./ft., Wall thickness or gauge No250	
TYPE OF SCREEN OR PERFORATION MATERIAL:			
✓ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)			
Brass Galvanized Steel None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)			
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)			
SCREEN-PERFORATED INTERVALS: From 290 ft. to 480 ft., From ft. to ft.			
From ft. to ft. From ft. to ft.			
GRAVEL PACK INTERVAL	S: From. 20 ft. to 220	ft., From . 280 ft. to . 480 ft.	
***	From ft. to	ft., From ft. to ft.	
6 GROUT MATERIAL: Neat co	ement Cement grout Bento:	nite Other	
		ft. to	
What is the nearest source of possible co	I lines Pit privy Livestock:	pens Insecticide storage Other (specify below)	
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well			
Watertight sewer lines Seepa	ge pit 🔲 Feedyard 🔲 Fertilizer s		
Direction from well NORTHWEST		from well 245' N & 170' W	
FROM TO LITHOL	OGIC LOG FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS	
OFF ATTACHED L			
SEE ATTACHED LO	DG		
7 CONTRACTOR'S OR LANDOWN	ER'S CERTIFICATION: This wat	er well was 🛮 constructed, 🗌 reconstructed, or 🗌 plugged	
under my jurisdiction and was completed on (mo/day/year) .3-23-12 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/year)3-26-12			
under the business name of MINTER-WILSON DRILLING CO., INC. by (signature) Torra Keller			
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367.			
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at			
http://www.kdheks.gov/waterwell/index.html.	and the second s		
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy			

33,187

The MINTER-WILSON DRILLING CO. Water Systems Professionals INCORPORATED and Domestic Water Systems Complete Installation and Repairing

Phone 620-276-8269 GARDEN CITY, KANSAS 67846 P.O. Box A •

NAME

STEVE STONE

COUNTY

FINNEY

DATE

1-10-12

LOCATION:

NW 1/4 17-26-33 - FROM STEVE'S MOM'S HOUSE - 1/2 MILE SOUTH,

1/4 MILE NORTHWEST

- SOUTH OF EXISTING WELL

STATIC WATER LEVEL -

TEST#1

0' TO 1' - TOP SOIL

1' TO 10' - BROWN SANDY CLAY

10' TO 15' - GRAY CLAY

15' TO 50' - FINE TO MEDIUM SAND & GRAVEL - TOOK WATER

50' TO 70' - BROWN CLAY

70' TO 170' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

170' TO 178' - GRAY CLAY WITH STRIPS OF WHITE ROCK

178' TO 267' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE WITH STRIPS OF BROWN CLAY

267' TO 278' - BROWN SANDY CLAY

278' TO 295' - FINE TO MEDIUM SAND & GRAVEL

295' TO 360' - BROWN SANDY CLAY WITH STRIPS OF WHITE ROCK

360' TO 372' - BROWN CLAY

372' TO 380' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 25%

380' TO 397' - BROWN CLAY

397' TO 401' - FINE TO MEDIUM SAND

401' TO 416' - BROWN CLAY

416' TO 444' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 15%

444' TO 460' - BROWN SANDY CLAY WITH 10% BROWN ROCK

460' TO 470' - BROWN & YELLOW CLAY WITH 25% BROWN ROCK

470' TO 480' - HARD BROWN & YELLOW CLAY WITH 10% BROWN ROCK

480' TO 500' - SHALE - 250 PULL DOWN