WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL:	Fraction	Section Number Township No. Range Number
County: FINNEY	NC 1/4 N1/2 1/4 S1/2 1/4 NE 1/2	4 30 T 26 S R 33 □E 🗹 W
Street/Rural Address of Well Location	n; if unknown, distance & direction	Global Positioning System (GPS) information:
from nearest town or intersection: If at owner's address, check here .		Latitude: 37.76152 (in decimal degrees)
GARDEN CITY-12 M. S. TO TV RD, 5 M. W. TO STONE RD,		Longitude:100.96651 (in decimal degrees)
2 M. S., 3,710 FT. N. & 1,320 FT. W.		Elevation:
2 WATER WELL OWNER: STEVE & RHONDA STONE		Collection Method:
012	5 S. SANDHILL ROAD	GPS unit (Make/Model: GARMIN 625T.*)
mil m marris m 1	DEN CITY, KS. 67846	Digital Map/Photo, Topographic Map, Land Survey
GARI	JEN CITT, NG. 67646	Est. Accuracy:
3 LOCATE WELL 525		
WITH AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered (1)		
SECTION BOX: Depth(s) Grown WELL'S STA	indwater Encountered (1)	t. (2)
WELL'S STA	ATIC WATER LEVEL	ft. after hours pumping gpm
DOT VIDID	mp test data: Well water was	ft. after hours pumping gpm
NW NE D II-1- D:		ft., andft.
W E Bore Hole Di	ER TO BE USED AS: Public w	ater supply Geothermal Injection well
Domostic	Feedlot	ter supply Dewatering Other (Specify below)
SW SE	☐ Industrial ☐ Domestic-l	awn & garden Monitoring well
Was a chemic	cal/bacteriological sample submitted	to Department? Yes No
	no/day/yr sample was submitted	
	sinfected? Yes No	
5 TYPE OF CASING USED: Steel PVC Other		
CASING JOINTS: Glued Clamped Welded Threaded		
Casing diameter 16 in. to 290 ft., Diameter in. to ft., Diameter in. to 550		
Casing height above land surface. 12 in., Weight 42.05 lbs./ft., Wall thickness or gauge No250		
TYPE OF SCREEN OR PERFORATION MATERIAL:		
✓ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)		
Brass Galvanized Steel None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:		
Continuous slot ✓ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☑ Wire wrapped ☐ Saw cut ☐ Other (specify)		
SCREEN-PERFORATED INTERVALS: From		
From ft. to ft. From ft. to ft.		
GRAVEL PACK INTERVALS: From 20 ft. to 210 ft., From 270 ft. to 525 ft.		
From ft. to ft. From ft. to ft.		
6 CROUT MATERIAL: Neat cement VI Cement grout Bentonite Other		
Grout Intervals: From 0 ft. to 20 ft., From 210 ft. to 270 ft., From ft. to ft.		
What is the nearest source of possible contamination:		
Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☑ Abandoned water well		
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well		
Direction from well NORTH		be from well _265.FT.
	OGIC LOG FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS
TROW TO BITTOE	0010 100	
SEE ATTACHED LO	OG	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged		
under my jurisdiction and was completed on (mo/day/year)3-23-12 and this record is true to the best of my knowledge and belief.		
Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/year) 3-20-12		
under the business name of MINTER-WILSON DRILLING CO., INC. by (signature) 1024 Nelley)		
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies		
(white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. I nclude fee of \$5.00 for each constructed well. Vi sit us at		
http://www.kdheks.gov/waterwell/index.html.	The state of the s	
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy		

20,058

The Irrigation and Domestic Water Systems Professionals WINTER-WILSON DRILLING CO. Complete Installation and Professionals

Irrigation and Repairing

INCORPORATED

GARDEN CITY, KANSAS 67846 Phone 620-276-8269 P.O. Box A •

NAME

STEVE STONE

COUNTY

FINNEY

DATE

1-9-12

LOCATION:

NE 1/4 30-26-33 - IVANHOE & TV ROAD - 1 MILE SOUTH, 1 MILE EAST,

1/4 MILE SOUTH & 1/4 MILE WEST

- SOUTH OF EXISTING WELL

STATIC WATER LEVEL -

TEST#1

0' TO 1' - TOP SOIL

1' TO 52' - BROWN SANDY CLAY WITH LAYERS OF SAND

52' TO 105' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

WITH STRIPS OF BROWN SANDY CLAY

105' TO 122' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

WITH LAYERS OF BROWN SANDY CLAY

122' TO 130' - BROWN SANDY CLAY

130' TO 162' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY

162' TO 177' - BROWN CLAY

177' TO 220' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN CLAY

220' TO 260' - BROWN SANDY CLAY & SAND & GRAVEL LAYERED

260' TO 276' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 20%

276' TO 285' - FINE TO MEDIUM SAND & GRAVEL

WITH LAYERS OF BROWN SANDY CLAY-30% - DRILLED TIGHT

285' TO 308' - FINE TO MEDIUM SAND & GRAVEL

308' TO 315' - BROWN SANDY CLAY

315' TO 325' - FINE TO MEDIUM SAND & GRAVEL

325' TO 330' - BROWN SANDY CLAY

330' TO 335' - BROWN SANDY CLAY WITH STRIPS OF SAND & GRAVEL - 30%

335' TO 350' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 20%

350' TO 356' - BROWN SANDY CLAY

356' TO 363' - FINE TO MEDIUM SAND & GRAVEL

363' TO 420' - BROWN SANDY CLAY WITH STRIPS OF WHITE ROCK

420' TO 463' - BROWN CLAY WITH STRIPS OF SAND - 10%

463' TO 480' - FINE TO MEDIUM SAND & GRAVEL

WITH 10% BROWN ROCK & 20% BROWN SANDY CLAY

480' TO 493' - BROWN SANDY CLAY WITH 10% BROWN ROCK

493' TO 502' - BROWN CLAY

502' TO 510' - HARD BROWN CLAY WITH 30% BROWN ROCK

510' TO 522' - HARD BROWN CLAY WITH 20% BROWN ROCK

522' TO 530' - SHALE - 250 PULL DOWN