

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Finney	SE 1/4 SW 1/4 NE 1/4	1	T 26 S	R 34 E

Distance and direction from nearest town or city street address of well if located within city?

Sublette, Ks: 19 North to Parallel Rd. go 6 West .5 South and West into

2 WATER WELL OWNER:	EOG Resources Inc	1-1 Jo Cattle Co
RR#, St. Address, Box # :	3817 NW Expressway Ste. 500	Board of Agriculture, Division of Water Resources
City, State, ZIP Code :	Oklahoma City, Ok 73112-1483	Application Number: 2006 0084

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	5 ELEVATION:
	Depth(s) Groundwater Encountered 1 212 ft. 2 237 ft. 3 100 ft. WELL'S STATIC WATER LEVEL 212 ft. below land surface measured on mo/day/yr 3-14-06 Pump test data: Well water was 237 ft. after 1 hours pumping 100 gpm Est. Yield 100 gpm: Well water was 237 ft. after 1 hours pumping 100 gpm WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well	ft. ELEVATION: 100 Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	7 Fiberglass		Threaded
3 RMP (SR)			
4 ABS			
Blank casing diameter 6 in. to 360 ft., Dia			
Casing height above land surface +2 in., weight 4.074 lbs./ft. Wall thickness or gauge No. SDR 21.316			
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	8 RMP (SR)	10 Asbestos-Cement
1 Steel	6 Concrete tile	9 ABS	11 Other (Specify)
2 Brass			12 None used (open hole)
3 Stainless Steel			
4 Galvanized Steel			
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot			
4 Key punched			
SCREEN-PERFORATED INTERVALS:	From 300 ft. to 360 ft.	From 300 ft. to 360 ft.	From 300 ft. to 360 ft.
GRAVEL PACK INTERVALS:	From 160 ft. to 360 ft.	From 160 ft. to 360 ft.	From 160 ft. to 360 ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other hole plug
Grout Intervals:	From 1 ft. to 25 ft.	From 1 ft. to 25 ft.	From 1 ft. to 25 ft.	From 1 ft. to 25 ft.
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	15 Oil well/Gas well
Direction from well?	South			12 Fertilizer storage
				13 Insecticide storage
				14 Abandoned water well
				16 Other (specify below)
				How many feet? 250

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Surface			
2	38	Sandy clay and clay streaks			
38	65	Sand and gravel			
65	80	Clay			
80	124	Sandy clay			
124	178	Sand			
178	211	Clay			
211	218	Sandy clay			
218	276	Sand and gravel			
276	302	Sandy clay and clay			
302	339	Sand			
339	350	Clay			
350	355	Sand			
355	360	Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-14-06 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No KWWCL 430 This Water Well Record was completed on (mo/day/yr) 3-14-06 under the business name of Howard Drilling Co Box 806 Beaver, Ok 73932 by (signature) <i>Phil Harnel</i>
