WATER WELL RECORD	Form WWC-	-5	Division	n of Water	r Resources; App. No.∟	
1 LOCATION OF WATER WEL	I		Section N	umber	Township Number	
	NW 1/4 NW 1/4 N		11		T 26 S	R 34 EW
Distance and direction from nearest town or city street address of well if Global Positioning Systems (decimal degrees, min. of 4 digits)						
located within city? Bridge S.	of Holcomb, 4 M. S.,1	M.W.,	Latitude:			
6 M. S., 3/4 M. E., 2½ M. S., 4910' N. & 4835' W. Longitude:						
2 WATER WELL OWNER: Who	eatland Electric Cooper	ative	Flevation	. —		
2 WATER WELL OWNER: Wheatland Electric Cooperative RR#, St. Address, Box # : PO Box 230 Inc. Datum:						
				1	<i>f</i> - 41 1	
Data Conection Method.						
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL						
LOCATION						
WITH AN "X" IN Depth(s) Groundwater Encountered (1)						
SECTION BOX: WELL'S STATIC WATER LEVEL236 ft. below land surface measured on mo/day/yr11-24-08						
N Pump test data: Well water wasft. after hours pumping gpm						
Est. Yieldgpm: Well water wasft. after hours pumpinggpm						
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well						
WELL WATER TO BE USED AS: 3 Fublic water supply 8 Air conditioning 17 injection well 2 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)						
W						
Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yrs						
Sample was submitted Water well disinfected? Yes No. X						
Sample was submitted						
5 TYPE OF CASING USED:				CASINO	G JOINTS: Glued	
(1)Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) WeldedXX						
2 PVC 4 ABS 7 Fiberglass						
Blank casing diameter 16 in. to 282 ft., Diameter in. to ft., Diameter ft.						
Casing height above land surface						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1)Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)						
2 Brass 4 Galvanized Steal 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)						
SCREEN OR PERFORATION OPEN	VINGS ARE:	,				
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)						
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw cut 10 Other (specify)						
SCREEN-PERFORATED INTERVALS: From 282 ft. to 457 ft., From ft. to ft.						
From						
GRAVEL PACK INTERVALS: From						
From. ft. to ft., From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 9 ft. to 25 ft., From 205 ft. to 265 ft., From ft. to ft.						
Grout Intervals: From 0	ft to 25 ft From	205	t to 2	65 fi	From	ft to ft
What is the nearest source of possible				A4	, 1 10111	10. 00
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide storage 16 Other (specify						
		11 Fuel sto			andoned water well	below)
						,
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/gas well Direction from well? How many feet?						
					DI LICODIO DIT	EDVALC
FROM TO LI	THOLOGIC LOG	FROM	TO		PLUGGING INT	EKVALS
See attache	ed log					
	1.4.4.4.4.4.4.4.4.4.4.4.4.4.4.4.4.4.4.4		-			
			<u> </u>	5 —	1 (2)	1 (2) 1
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged						
under my jurisdiction and was completed on (mo/day/year) 11-24-08 and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No 208 This Water Well Record was completed on (mo/day/year) 11-25-08						
under the business name of Minter-Wilson Drilling Co. , Inc. by (signature) Month Hollin INSTRUCTIONS : Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top						
INSTRUCTIONS : Use typewriter or ball po	oint pen. PLEASE PRESS FIRMLY and I	PRINT clearl	y. Please fi	ll in blanks	s, underline or circle the c	
three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone						
785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.						
i month in the straightful that well indeath in the						

MINTER-WILSON DRILLING CO. Water Systems Complete Installation

Irrigation and Domestic

INCORPORATED

Phone 276-8269

P.O. Box A

GARDEN CITY, KANSAS 67846

NAME

WHEATLAND ELECTRIC

COUNTY

FINNEY

DATE

4-24-08

LOCATION:

NW 1/4 11-26-34 - FROM PARALLEL & IVANHOE ROAD

1-1/2 MILES SOUTH, 1-3/4 MILES WEST

& 1/8TH OF A MILE SOUTHWEST

- 1300 FT. NORTHWEST OF PIVOT

NW11-TH 5-08 - NORTHWEST EDGE OF CIRCLE

STATIC WATER LEVEL - 234 FT.

0' TO 1' - TOP SOIL

1' TO 22' - FINE SAND - LOOSE

22' TO 49' - BROWN CLAY

49' TO 74' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

74' TO 77' - BROWN CLAY

77' TO 105' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE WITH STREAKS OF BROWN CLAY

105' TO 116' - BROWN CLAY

116' TO 124' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

124' TO 157' - BROWN CLAY WITH STREAKS OF SAND & GRAVEL

157' TO 164' - FINE TO MEDIUM SAND & GRAVEL

164' TO 188' - FINE SAND WITH SANDY BROWN CLAY MIXED

188' TO 218' - FINE TO MEDIUM SAND & GRAVEL

218' TO 232' - BROWN SANDY CLAY WITH STREAKS OF SAND

232' TO 251' - FINE TO MEDIUM SAND & GRAVEL

WITH STREAKS OF BROWN CLAY 20%

251' TO 254' - BROWN CLAY

254' TO 262' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE WITH STREAKS OF BROWN CLAY 10%

262' TO 265' - BROWN CLAY

265' TO 276' - FINE TO MEDIUM SAND & GRAVEL

WITH STREAKS OF BROWN CLAY 10%

276' TO 282' - BROWN CLAY

282' TO 321' - FINE TO MEDIUM SAND & GRAVEL

WITH STREAKS OF BROWN CLAY 10%

321' TO 403' - BROWN CLAY WITH STREAKS OF SAND & GRAVEL

20% GRAVEL

403' TO 415' - BROWN ROCK, YELLOW CLAY & BROWN CLAY MIXED

415' TO 420' - RED CLAY - 300 PULL DOWN

420' TO 427' - YELLOW CLAY - 300 PULL DOWN

427' TO 454' - HARD BROWN CLAY & GRAY SHALE

- SOME BROWN ROCK 10% - 300 PULL DOWN