	RD	Form WW	C-5	Division of Wate	er Resources; App. No.	22,576
1 LOCATION OF WATER WELL:		Fraction		Section Number	Township Number	Range Number
County: Finney		SE 1/4 SE 1/4			T 26 S	R 34 E(W)
Distance and direction from nearest town or city street address of well if located within city? Garden City - 14 miles S. to Lear Latitude:						
	•			Latitude:		
RD., 7 miles W, 2,9 2 WATER WELL OWNE		Electric Co		Longitude:		
RR#, St. Address, Box #			op, inc.	Datum:		
		y, KS 67871		Data Collection	Method:	
3 LOCATE WELL'S 4	DEPTH OF COMP	•	5			
LOCATION						
WITH AN "X" IN DO	epth(s) Groundwater	Encountered (1	l)	ft. (2)	ft. (3).	ft.
SECTION BOX: W	ELL'S STATIC WA	TER LEVEL?	62 ft	below land surface	e measured on mo/day	y/yr2 25 09
	st. Yieldgpm	: Well water was	,	II. aner ft after	hours pumping.	onm
	ELL WATER TO BI					
$ \mathbf{w} ^{-\frac{NW}{1}} \mathbf{v} ^{-\frac{NE}{1}} _{E} _{1}$	Domestic 3 Feed	dlot 6 Oil fi	ield water su	apply 9 Dev	vatering 12 O	ther (Specify below)
	Irrigation 4 Indu	ustrial 7 Dom	estic (lawn	& garden) 10 Mon	nitoring well	
SW SE	/	-1:11	مه ادمهانسیان	Danasturant? Vas	No X	If you madday/yma
	as a chemical/bacteri ample was submitted.					
s	impre was saoimited.		****	or wen disinicoted.	105	
5 TYPE OF CASING USE	D: 5 Wrought I	ron 8 C	oncrete tile	CASIN	G JOINTS: Glued	Clamped
Steel 3 RMP (S	SR) 6 Asbestos-6	Cement 9 O	ther (specify	below)	Welded.	XX
2 PVC 4 ABS	7 Fiberglass				Threade	d
Blank casing diameter	in. to293	ft., Diameter.	42 O5	in. to ft.,	Diameter	in. toft.
Casing height above land sur TYPE OF SCREEN OR PER			74.4.9.7	.ibs./it. wan thi	ckness or guage No.	
			9 /	ABS	11 Other (Specify)	
2 Brass 4 Galvan	ized Steal 6 Concr	rete tile 8 RM				
SCREEN OR PERFORATION						
1 Continuous slot	Mill slot 5 Ga	auzed wrapped	7 Torch cut	9 Drilled holes	11 None (open)	nole)
2 Louvered shutter 4 SCREEN-PERFORATED IN	JTERVALS: From	295 ft.	515	ft. From	y) ft. to .	ft.
	From	ft. 1	to	ft., From	ft. to .	ft.
GRAVEL PACK IN	TERVALS: From					
	From	ft. 1	to	ft., From	ft. to .	ft.
6 GROUT MATERIAL:	1 Neat cement (2)	Cement grout 3	Bentonite	4 Other		
Grout Intervals: From .	1 Neat cement (2) 1 Neat cement (2)	20 ft., From	215	ft. to 275 f	t., From	ft. toft.
What is the nearest source of						
1 Septic tank	7 Pit privy	10 Livest		secticide storage	16 Other (specify below)	
		8 Sewage lagoon 9 Feedyard	11 Fuel s	zer storage 15 Oi	bandoned water well l well/gas well	ŕ
Direction from well?	Southeast		How mar	ny feet? 200 ft.	south & 200 f	t. east
FROM TO	LITHOLOGIC	LOG	FROM	TO	PLUGGING INT	ERVALS
See	attached log					
	0					
7 CONTRACTOR'S OR L	ANDOWNER'S CE	RTIFICATION	This water	well was (1) const	ructed, (2) reconstruc	eted, or (3) plugged
under my jurisdiction and wa	as completed on (mo/o	day/year) 2 2	2 6-09 and	d this record is true	to the best of my kno	wledge and belief.
Kansas Water Well Contract	or's License No 2	2 08 This Wa	iter Well Re	cord was completed	d on (mo/day/year)	2-26-09
under the business name of	Minter-Wils	on Drlg. Co.	Inc. b	y (signature) 10	rakeller	G1
INSTRUCTIONS: Use typewriter three copies to Kansas Department	of Health and Environmen	nt, Bureau of Water, G	eology Section	n, 1000 SW Jackson St.,	Suite 420, Topeka, Kansa	as 66612-1367. Telephone
785-296-5522. Send one to	WATER WELL OWN	ER and retain one	for your r	records. Fee of \$5	.00 for each construct	ed well. Visit us at
http://www.kdheks.gov/waterwell/ir	idex.nimi.					

The Professionals MINTER-WILSON DRILLING CO. Water Systems Complete Installation

Irrigation and Repairing

INCORPORATED

Phone 620-276-8269 P.O. Box A • **GARDEN CITY, KANSAS 67846**

NAME

WHEATLAND ELECTRIC - CIRCLE # E3

COUNTY

FINNEY

DATE

1-7-09

LOCATION:

NW 1/4 26-26-34 - PARALLEL & IVANHOE ROAD - 3-1/2 MILES

SOUTH, 1-1/2 MILES WEST & 1-3/8THS

MILES SOUTH

STATIC WATER LEVEL -

TEST #1

O' TO 7' - FINE SAND

7' TO 32' - SANDY BROWN CLAY

32' TO 36' - WHITE SANDY CLAY

36' TO 48' - BROWN SANDY CLAY

48' TO 115' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

115' TO 120' - WHITE CLAY

120' TO 168' - BROWN SANDY CLAY WITH STREAKS OF WHITE CLAY

168' TO 170' - HARD WHITE CLAY - PULL DOWN 300

170' TO 186' - BROWN SANDY CLAY WITH STREAK OF FINE SAND

186' TO 193' - FINE TO MEDIUM SAND & GRAVEL

193' TO 219' - BROWN SANDY CLAY WITH STREAK OF SAND & GRAVEL

219' TO 234' - HARD BROWN CLAY

234' TO 274' - BLUE CLAY

274' TO 278' - YELLOW SAND CLAY

278' TO 302' - MEDIUM & COARSE GRAVEL WITH STREAKS OF BLUE CLAY

302' TO 311' - MEDIUM & COARSE GRAVEL WITH LAYERS OF BROWN CLAY

311' TO 323' - BROWN SANDY CLAY

323' TO 326' - MEDIUM & COARSE GRAVEL

326' TO 339' - BROWN SANDY CLAY

339' TO 344' - FINE & MEDIUM SAND & GRAVEL

344' TO 353' - BROWN SANDY CLAY WITH STREAKS OF SAND

353' TO 364' - FINE & MEDIUM SAND & GRAVEL WITH STREAKS OF **BROWN SANDY CLAY**

364' TO 376' - BROWN CLAY

376' TO 448' - SANDY BROWN CLAY

448' TO 454' - FINE TO MEDIUM SAND & GRAVEL

454' TO 477' - BROWN CLAY WITH STREAKS OF SAND

477' TO 485' - FINE TO MEDIUM SAND & GRAVEL

485' TO 491' - BROWN ROCK

491' TO 502' - BROWN CLAY - BROWN ROCK 30%

502' TO 506' - BROWN ROCK

506' TO 535' - BROWN CLAY

535' TO 545' - GRAY SHALE