WATER WELL RECORD			Form WWC-	5	Divisio	n of Wate	r Resources; App. No. L	22,373	
1 LOCATION OF WATER WELL:			Fraction					Range Number	
County:	Finne			SW 1/4	T 26 S R 34 Global Positioning Systems (decimal degrees, min. of 4			R 34 EW	
1 to 1 to 1 to 1 to 0 m at the material and many the material To 1 to 1									
S. to Paral	lel RD	, 1-3/4 M. E., 2-	Latitude:						
2 WATER WELL OWNER: Wheatland Electric 4690' W.						Elevation:			
RR#, St. Address, Box # : Cooperative, Inc. PO Box 230						Datum:			
City, State,	KS 67871		Data Collection Method:						
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL									
LOCATION									
WITH AN "X" IN Depth(s) Groundwater Encountered (1)									
SECTION I	SECTION BOX: WELL'S STATIC WATER LEVEL252ft. below land surface measured on mo/day/yr3-7-09								
Pump test data: Well water wasft. after									
	WELL WATER TO BE LISER AS, 5 Public quotes supply 9 Air conditioning 11 Injection well								
WELL WATER TO BE USED AS: 3 Public water supply 8 Air conditioning 11 injection went Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)									
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well									
Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yrs									
Sample was submitted									
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped									
1)Steel		P (SR) 6 Asbestos-				CASING		Clamped	
2 PVC	4 ABS	7 Fiberglass		F	row. 300	. Ft	Threaded		
2 PVC 4 ABS 7 Fiberglass									
Blank casing diameter 16 in to 260 ft., Diameter 16 in to 340 ft., Diameter in to ft. Casing height above land surface 12 in., Weight 42.05 lbs./ft. Wall thickness or guage No 250									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 260 ft. to 300 ft., From 340 ft. to 470 ft.									
From									
From									
t. to the first term of the total state of of the total stat									
	TERIAL	: 1 Neat cement (2)	Cement grout 3 Ber	ntonite	4 Other				
Grout Intervals:		m 0 ft. to		. 185	ft. to	242 ft	., From	ft. toft.	
What is the nearest source of possible contamination: 1. Sertia toul. 1. A Letteral lines 7. Pit print.									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide storage 16 Other (speci 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well below)								below)	
		lines 6 Seepage pit			er storage				
							N/A		
FROM TO		LITHOLOGIC	LOG	FROM	ТО		PLUGGING INT	ERVALS	
	Con attached log								
		See attached log							

T CONTRIB A CITION OF LANDON AND ON CHEMICAL THON THE CONTRIBUTION OF THE CONTRIBUTION									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-709 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No208 This Water Well Record was completed on (mo/day/year)									
under the business name of Minter-Wilson Drilling Co., Inc. by (signature) Nora Heller									
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks, underline or circle the correct answers. Send top									
three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at									
http://www.kdheks.gov/waterwell/index.html.									

The Professionals

MINTER-WILSON DRILLING CO. Water Systems Complete Installation

Irrigation
and Domestic
Water Systems
Complete Installation
and Repairing

INCORPORATED

Phone 276-8269

P.O. Box A

GARDEN CITY, KANSAS 67846

NAME

WHEATLAND ELECTRIC - CIRCLE #G96

COUNTY

FINNEY

DATE

9-26-08

LOCATION:

SW 1/4 12-26-34 - HOLCOMB LANE SOUTH TO IVANHOE ROAD -

2-1/2 MILES SOUTH, 1/2 MILE WEST,

1/2 MILE NORTH, 3/8THS OF A MILE WEST FOLLOW CIRCLE - NW EDGE OF CIRCLE

STATIC WATER LEVEL - 225 FT.

TEST#3

0' TO 1' - TOP SOIL

1' TO 27' - BROWN SANDY CLAY

27' TO 59' - BROWN CLAY

59' TO 71' - FINE TO MEDIUM SAND & GRAVEL

71' TO 130' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

130' TO 141' - BROWN CLAY

141' TO 166' - FINE TO MEDIUM SAND & GRAVEL - 10% CLAY

166' TO 186' - BROWN SANDY CLAY

186' TO 248' - FINE TO MEDIUM SAND & FINE GRAVEL

248' TO 294' - FINE TO MEDIUM SAND & GRAVEL WITH CLAY STREAKS

294' TO 319' - BROWN CLAY

319' TO 334' - BROWN SANDY CLAY

334' TO 374' - BROWN CLAY - STICKY

374' TO 389' - BROWN CLAY

389' TO 391' - FINE TO MEDIUM SAND

391' TO 407' - BROWN CLAY WITH STREAKS OF GRAVEL

407' TO 455' - BROWN CLAY

455' TO 457' - BROWN ROCK

457' TO 463' - BROWN YELLOW CLAY

463' TO 467' - YELLOW CLAY

467' TO 485' - SHALE - HARD PULL DOWN