WATER WELL RECORD)	Form W	WC-5	Division of Wate	r Resources App. No	22,577	
1 LOCATION OF WATER W	/ELL:	Fraction		Section Number	Township No.	Range Number	
County: FINNEY		1/4 NW 1/4 SE		24	T 26 S	R 34 □E 🗹 W	
Street/Rural Address of Well Location, if unknown, distance & direction				Global Positioning			
from nearest town or intersection: If at owner's address, check here				Latitude: (in decimal degrees) Longitude: (in decimal degrees)			
GARDEN CITY-13-1/3 MILES SOUTH ON HWY 83 TO CRAFT				Elevation:			
RD, 6 MILES WEST, 1035 FT N-3660 FT W.				<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27			
2 WATER WELL OWNER: WHEATLAND ELECTRIC COOP INC				Collection Method:			
RR#, Street Address, Box #: P O BOX 230 City, State, ZIP Code : SCOTT CITY, KANSAS 67871			☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
City, Said, Zii Coto	SCOTT	CITT, KANSAS 678	371	Est. Accuracy:	3 m, 3-5 m,	5-15 m, >15 m	
3 LOCATE WELL			- 475				
					6 (1	2) A	
N WELL	OX: Depth(s) Groundwater Encountered (1)						
	Pump test data: Well water wasft. after hours pumping gpm						
EST. YIELDgpm. Well water was							
W E Bore Hole Diameter							
WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well SW SE ☐ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below)							
swse							
Was a chemical/bacteriological sample submitted to Department? Yes No							
S If yes, mo/day/yr sample was submitted							
1 mile Water	well disinf	fected? 🗌 Yes 🔽	No				
5 TYPE OF CASING USED:	▼ Steel	□ PVC □	Other		••••	· · · · · · · · · · · · · · · · · · ·	
CASING JOINTS: Glued Clamped Welded Threaded							
Casing diameter 16 in. to							
Casing height above land surface. 12. in., Weight 42.05. lbs./ft., Wall thickness or gauge No250							
TYPE OF SCREEN OR PERFORATION MATERIAL: ☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)							
Brass Galvanized Steel None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
☐ Continuous slot							
SCREEN-PERFORATED INTERVALS: From 270 ft. to 475 ft., From ft. to ft.							
From ft. to ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From 20 ft. to 200 ft., From 260 ft. to 475 ft. From ft. to ft., From ft., From ft. to ft.							
6 GROUT MATERIAL:	Nost same	rt 7 Coment cross	t. to			io It.	
Grout Intervals: From0	Near ceme	20 ft From	. 200	to 260 ft	From	. ft. toft.	
What is the nearest source of pos					110111	. 10 00	
Septic tank] Lateral line	es 🔲 Pit privy	Livestock p		storage	er (specify below)	
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☑ Abandoned water well ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well							
☐ Watertight sewer lines ☐ Direction from well NORTH	WEST	it Feedyard		from well		***************************************	
	THOLOG	IC LOG	FROM			GGING INTERVALS	
			1			 	
SEE ATTACH	IED LOG		1				
			+			······································	
			<u> </u>				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed, reconstructed, or plugged							
under my jurisdiction and was completed on (mo/day/year) 4-29-11							
under the business name of MINTER-WILSON DRILLING CO., INC. by (signature)							
INSTRUCTIONS: Use typewriter or b	all point pen.	PLEASE PRESS FIRML	Y and PRINT cle	arly. Please fill in blanks	and check the correct	answers. Send three copies	
(white, blue, pink) to Kansas Department Telephone 785-296-5522. Send one co	nt of Health	and Environment, Bureau	of Water, Geold	gy Section, 1000 SW Ja	ckson St., Suite 420, 7	Fopeka, Kansas 66612-1367.	
http://www.kdheks.gov/waterwell/index.l		LR WELL OWNER and	Totali one for y	our records. Include <u>les</u>	or abyon for each Co	ORGANICIO WEIL VISILUS AL	
KSA 82a-1212				Check: W	nite Copy, 🔲 Blu	ie Copy, 🔲 Pink Copy	

22,577

The Professionals MINTER-WILSON DRILLING CO. Water Systems Complete Installation

Irrigation and Repairing

INCORPORATED

Phone 620-276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

NAME

WHEATLAND ELECTRIC - CIRCLE # G122

COUNTY

FINNEY

DATE

1-18-11

LOCATION:

SW 1/4 24-26-34 - IVANHOE & TV ROAD - 1/2 MILE WEST,

3/4 OF A MILE SOUTH & 1/4 OF A MILE WEST

- 300 FT. SOUTH OF EXISTING WELL

STATIC WATER LEVEL -

TEST#3

0' TO 3' - FINE SAND

3' TO 35' - BROWN SANDY CLAY

35' TO 118' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

118' TO 140' - BROWN SANDY CLAY

140' TO 155' - BROWN CLAY

155' TO 162' - BROWN SANDY CLAY WITH LAYERS OF SAND & GRAVEL

162' TO 194' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

WITH LAYERS OF BROWN SANDY CLAY

194' TO 243' - BLUE CLAY

243' TO 251' - FINE TO MEDIUM SAND

251' TO 258' - BLUE CLAY

258' TO 270' - FINE TO MEDIUM SAND WITH STRIPS OF BLUE CLAY - 20%

270' TO 277' - BROWN SANDY CLAY

277' TO 280' - FINE TO MEDIUM SAND & GRAVEL

280' TO 289' - BROWN SANDY CLAY WITH LAYERS OF SAND & GRAVEL - 30%

289' TO 301' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 20%

301' TO 306' - BROWN SANDY CLAY WITH STRIPS OF SAND & GRAVEL - 10%

306' TO 318' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 10%

318' TO 330' - BROWN SANDY CLAY WITH STRIPS OF SAND & GRAVEL - 30%

330' TO 337' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 20%

337' TO 351' - BROWN SANDY CLAY WITH STRIPS OF SAND & GRAVEL - 10%

351' TO 357' - FINE TO MEDIUM SAND & GRAVEL

357' TO 378' - BROWN SANDY CLAY WITH STRIPS OF WHITE ROCK

378' TO 384' - FINE TO MEDIUM SAND

384' TO 435' - BROWN CLAY & BROWN SANDY CLAY MIXED

WITH STRIPS OF WHITE ROCK

435' TO 438' - FINE TO MEDIUM SAND WITH 10% BROWN ROCK

438' TO 440' - BROWN CLAY

440' TO 444' - FINE TO MEDIUM SAND WITH 10% BROWN ROCK

444' TO 460' - BROWN SANDY CLAY

460' TO 468' - HARD BROWN & YELLOW CLAY WITH 40% BROWN ROCK

468' TO 473' - HARD BROWN, YELLOW & RED CLAY WITH 40% BROWN ROCK - 300 PULL DOWN

473' TO 500' - SHALE - 300 PULL DOWN