WATER WELL RECORD	Form WWC-5	Division of Wate	er Resources App. No.	30,157
1 LOCATION OF WATER WELL:	Fraction	Section Number		Range Number
County: Finney	1/4 NW 1/4 SE 1/4 NW 1/4	25		R 34 DE X W
Street/Rural Address of Well Location;			g System (GPS) info	
from nearest town or intersection: If at owner's address, check here Latitude: Longitude: Longitude				
East to Ivanhoe RD, 4-1/3 M				
	tland Electric Coop, Ir	☐ Datum: ☐ WGS 8	4, 🔲 NAD 83, 🔲	NAD 27
man at the control of	ox 230		ke/Model:)
O'L OLL GID OLL	t City, Kansas 67871	Digital Map/Pl	hoto, 🗌 Topographic	Map, Land Survey
3 LOCATE WELL		Est. Accuracy:	<3 m, 3-5 m, 5	5-15 m, <u></u> >15 m
WITH AN "X" IN 4 DEPTH OF	COMPLETED WELL	495 ft.		
SECTION BOX: Depth(s) Groundwater Encountered (1)				
N WELL'S STATIC WATER LEVEL291ft. below land surface measured on mo/day/yr.61811 Pump test data: Well water was				
POT MITTED WITH A CO. I The Co. I Th				
Well water was				
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well				
SW SE ☐ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below) ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well				
Was a chemical/bacteriological sample submitted to Department? Yes X No				
If yes, mo/day/yr sample was submitted				
1 mile Water well disi	nfected? 🗌 Yes 🕱 No			
5 TYPE OF CASING USED: X Stee	el PVC Other	EDOM 270 E		
CASING JOINTS: Glued Clamped Welded Threaded FROM 370 FT. Casing diameter 16 in to 280 ft., Diameter 16 in to 410 ft., Diameter in to ft.				
Casing height above land surface	12 in Weight 42.05	lbs./ft Wall thi	ckness or gauge No	.250
Casing height above land surface12				
X Steel Stainless Steel PVC Other (Specify)				
Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:				
☐ Continuous slot 🕱 Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)				
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)				
From				
GRAVEL PACK INTERVALS:	From)0 ft., From .	26.0 ft. t	to 495 ft.
COLONE MARRIANA FINA	From ft. to	ft., From .	ft. t	o ft.
6 GROUT MATERIAL: Neat cen Grout Intervals: From 0 ft.	to 20 ft., From 200			
What is the nearest source of possible con		16. 60 200 16.	, 110m	. 10. 10
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)				
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well				
Direction from well Northwes		from well 175	Ft. North &	240 Ft. West
FROM TO LITHOLO	GIC LOG FROM	TO LITHO, I	LOG (cont.) <u>or</u> PLU	GGING INTERVALS
See attach	ed log			
		,		

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ▼ constructed, □ reconstructed, or □ plugged				
under my jurisdiction and was completed on (mo/day/year) 6-18-11 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No 208 This Water Well Record was completed on (mo/day/year) 6-20-11				
under the business name of				
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies				
(white, blue, pink) to Kansas Department of Heal Telephone 785-296-5522. Send one copy to WA				
http://www.kdheks.gov/waterwell/index.html.				
KSA 82a-1212		Check: 🗹 V	vnite Copy, 🔲 Bli	le Copy, 🔲 Pink Copy

The Professionals MINTER-WILSON DRILLING CO. Water Systems Complete Installation and Professionals

Irrigation and Repairing

INCORPORATED

P.O. Box A • **GARDEN CITY, KANSAS 67846** Phone 620-276-8269

NAME

WHEATLAND ELECTRIC - CIRCLE # G124

COUNTY

FINNEY

DATE

1-20-11

LOCATION:

NW 1/4 25-26-34 - IVANHOE & TV ROAD - 1/2 MILE WEST,

1-1/4 MILES SOUTH & 1/4 MILE WEST - 300 FT. SOUTHEAST OF EXISTING WELL

STATIC WATER LEVEL - 250 FT.

TEST#2

0' TO 1' - TOP SOIL

5' - FINE SAND 1' TO

5' TO 55' - BROWN SANDY CLAY

55' TO 119' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

119' TO 150' - BROWN SANDY CLAY WITH STRIPS OF WHITE ROCK

150' TO 165' - FINE TO MEDIUM SAND & GRAVEL

WITH LAYERS OF BROWN SANDY CLAY

165' TO 200' - BROWN SANDY CLAY

200' TO 235' - BROWN SANDY CLAY WITH STRIPS OF SAND & GRAVEL

235' TO 257' - BROWN SANDY CLAY

257' TO 276' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 20%

276' TO 281' - BROWN SANDY CLAY & SAND & GRAVEL MIXED

281' TO 294' - FINE TO MEDIUM SAND & GRAVEL

294' TO 303' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF CLAY - 20%

303' TO 310' - FINE TO MEDIUM SAND & GRAVEL

310' TO 323' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY & WHITE ROCK - 30%

323' TO 328' - SOFT BROWN SANDY CLAY WITH STRIPS OF WHITE ROCK

328' TO 335' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 20%

335' TO 436' - BROWN SANDY CLAY WITH STRIPS OF WHITE ROCK

436' TO 439' - FINE TO MEDIUM SAND & BROWN ROCK - 10% 439' TO 451' - BROWN SANDY CLAY WITH STRIPS OF SAND & GRAVEL - 20%

451' TO 457' - FINE TO MEDIUM SAND & GRAVEL WITH SOME BROWN ROCK - 10%

457' TO 462' - BROWN SANDY CLAY

462' TO 467' - FINE TO MEDIUM SAND & GRAVEL WITH SOME BROWN ROCK - 20%

467' TO 491' - HARD BROWN & YELLOW CLAY WITH STRIPS OF BROWN ROCK - 30%

491' TO 500' - SHALE - 300 PULL DOWN