USE TYPEWRITE R BALL POINT PEN-P SIRMLY, PRINT CLEARLY.

## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

|  | County   | Fraction                              |   | Section number                          |     | Township number Range number   |   |                             |                  |
|--|--|---------------------------------------|---|---|-----|--|---|-----------------------------|------------------|
| 1. Location of well:   | Kearny   | SE 1/4 NW 1/4 SW                      | 1/4   | 2                                       |     | т 26 s   | <sub>R</sub> 35                                   | E.                          |                  |
| 2. Distance and direction from nearest town or city: ½ east of the  Deerfield river bridge, 12 south,  Street address of well location if in city: |  |                                       |   | er of well:<br>street:<br>tate, zip cod | ]   | Jack Campbell<br>Lakin, Ks. 6786   |   |                             |                  |
| 4. Locate with "X" in section below:  N  |  |                                       |   |   |     | 6. Bore hole dia. <u>26</u> in.<br>Well depth <u>336</u> ft.                                       | Completion date                                   | 5 <u>-10-</u> 17            |                  |
|  |  |                                       |   |   |     | 7 Cable tool Rotary Driven Dug Hollow rod Jetted Bored X Reverse rotary                            |   |                             |                  |
| W W  | E E  |                                       | 8. Use: Domestic Public supply Industry  X   Irrigation Air conditioning Stock Lawn Oil field water Other           |   |     |  |   |                             |                  |
| <b>y</b> sw  | SE<br>!  |                                       | 9. Casing: Material <u>Steel</u> Height: Above at tacks  Threaded Welded Surface in.  RMP PVC Weight 36 87 lbs./ft. |   |     |  |   |                             |                  |
| 5. Type and color of   |  |                                       | -   | From                                    | То  | Dia 16 in. to 337 ft. depth Wall Thickness: inches or Dia in. to ft. depth gage No 250             |   |                             |                  |
| 5. Type and color of material  |  |                                       |   | -                                       |     | 10. Screen: Manufacturer's name  |   |                             |                  |
|  |  |                                       | -   |   |     | Type galv.   |   |                             |                  |
|  |  |                                       |   |   |     | Slot/general 230-290 Set between 230-290 Perf:140-230 ft. a Gravel pack? Yes Size rar              | ft. and 310-32<br>nd 29 <b>0</b> -310             | 0 ft.<br>320-f <b>3.3</b> 6 | 5                |
|  |  |                                       |   |   |     | 11. Static water level:  97 ft. below land surf  | _ mo  | ./day/yr.<br>7 <b>–</b> 77  |                  |
|  |  |                                       |   |   |     | 12. Pumping level below land  133 ft. after 2 h  144 ft. after 4 h  Estimated maximum yield —      | rs. pumping 90 rs. pumping 125 1250               | Og.p.m.<br>Og.p.m.          |                  |
|  |  |                                       |   |   |     | 13. Water sample submitted:  | mo<br>Date  | ./day/yr.                   |                  |
|  |  |                                       |   | -                                       |     | 14. Well head completion: Pitless adapter  | 12 Inches above                                   | grade                       |                  |
|  |  | · · · · · · · · · · · · · · · · · · · |   |   |     | 15. Well grouted? <u>yes</u> With: Neat cement  Depth: From 0 ft. to _                             | Bentonite X                                       | Concrete _                  | \<br>\<br>\<br>\ |
|  |  |                                       |   |   |     | 16. Nearest source of possible ft Direction Well disinfected upon comple                           | Туре  | N/A<br>X No                 | lc               |
|  |  |                                       |   |   |     | 17. Pump:  Manufacturer's name Goul  |   | mp                          | ۱)<br>ا          |
|  |  |                                       |   |   |     | Model number 12 JHC Length of drop pipe 200 Type:  | _ HP <u>200</u> _ Vo<br>_ ft. capacity <u>120</u> | 00<br>g.p.m.                | 3                |
|  |  |                                       |   |   |     | Submersible  | X Turbin  |                             | 1                |
|  | (Use a second s                                      | heet if needed)                       |   |   |     | Jet<br>Centrifugal   | Kecipr  | rocating                    | , I              |
| 18. Elevation:   | 19. Remarks:   |                                       |   |   |     | 20. Water well contractor's of<br>This well was drilled under my<br>is true to the best of my know | y jurisdiction and thi                            | s report                    | .6               |
| Topography: Hill X Slope   |  |                                       |   | _                                       | ~~2 | Minter-Wilson I  | rilling Co  | 208 Acense No.              | 51/2 NW          |
| Upland Valley  | , i. <u>i. i. i</u> |                                       |   | >                                       | 40  | Signed Le Authorized repl  | Date Date   | 30-27                       | יט<br>אוגיי      |

Phone 276-8269 • P.O. Box 493 • GARDEN CITY, KANSAS 67846

MGK CAMPBELL KEARNY COUNTY 11-30-76

Location: 37 2-26-35 350 3t. south of #11

| Test        | 4-2         |   |
|-------------|-------------|---|
| 0           | 12          | Fine sand                                   |
| 12          | 133         | Bine to med. sand and gravel                |
| 183         | 260         | ිrovm clay                                  |
| 268         | 292         | Fine to med. sand and gravl                 |
| 292         | <b>3</b> 03 | ring to med. sand and gravel 20% clay tight |
| <b>3</b> 03 | 336         | ding to med. sand and gravel                |
| 335         | 410         | Drown sandy clay                            |