USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County Fraction		Section number		Township number	Range number			
1. Location of well:		1/4 1/4 <b>SE</b>		1	.9	T 26 s	<sub>R</sub> 35	E/W	
Distance and direct     On Hiway     Street address of well	25, 9 3/4 East, & location if in city:	South of Lakin North	R.R. or	ner of well street: tate, zip o		Walter Fletcher Lakin, KS 6786			
4. Locate with "X" i		Sketch map:	•			6. Bore hole dig. <b>26</b> in Well depth <b>306</b> ft.		<u>28-</u> 79	
NW	   NE					7 Cable tool Rotary Hollow rod Jetted	Driven Dug	e rotary	
						8. Use: Domestic Public supply Industry  X Irrigation Air conditioning Stock Lawn Oil field water Other			
- SW S	5K		9. Casing: Material <b>Stee!</b> Height: Above or below  Threaded Welded Surface 1 ft in.  RMP PVC Weight 36.87_lbs./ft.						
1 Mi						Dia. 16 in. to 306ft. dep	th Wall Thickness: inch	es or	
5. Type and color of	material			From	То	Dia in. to ft. dep			
	Casing Schedule					Type Johnson Gal	v.Di100-16"	<u> </u>	
	0 - 130 Plain				•	Slot/gauze			
	130 - 260 Perf. 260 - 300 Screen					Set betweenft. c	and		
	300 - 306 Perf.					Gravel pack? <b>Yes</b> Size ra	nge of material 2 t	<u>o 5/</u> 8	
						11. Static water level: ft. below land sur		day/yr.	
						12. Pumping level below land  113 ft. after2 h	surfaces:		
						119 ft. after 4 h	nrs. pumping 1500 g	g.p.m. g.p.m.	
						13. Water sample submitted:	2000	day/yr.	
						14. Well head completion:	ft Inches above gr	ade	
						15. Well grouted?	Bentonite <b>X</b> Co	ncrete	
**************************************	·····					16. Nearest source of possible	contamination:	[€	
						Well disinfected upon comple  17. Pump:  Manufacturer's name Goule	Not installed	= <sup>No</sup>   Bowl (	
						Model number	HP <u>125</u> Volts ft. capacit]1000 g	.p.m. &	
						Type: Submersible	X Turbine		
	(Use a second sh	neet if needed)				Jet Centrifugal	Reciproce	ating Sec.	
18. Elevation:	19. Remarks:					20. Water well contractor's of This well was drilled under my is true to the best of my know	y jurisdiction and this re	eport	
Topography: X Hill						Minter Wilson D	rilling Co.	<u>208</u> ∑ ⟨	
Slope						Address name Address A. Gard	en City, KS	* 67846	
Upland Valley					7	Authorized rep	resentative	Z	

P.O. Box A . GARDEN CITY, KANSAS 67846 Phone 276-8269 . January 19, 1979

Walter Fletcher Kearny County

Location: S. E. & 19-26-35 Static Water Level 110 Test # Pivot

)	39	Fine Sand
39	101	Med. to coarse gravel (loose)
101	110	Brown Clay
210	136	Med. to coarse gravel (loose)
236	155	Brown Clay
155	169	Fine to med. sand and gravel (loose)
169	239	Brown Clay
239	304	Fine to med. sand and gravel 10% Clay
		(100se)
304	320	Brown Clay
320	352	Brown Clay & White Rock (hard)
35 <b>2</b>	365	Brown Sandy Clay streaks of gravel 30%
		(Fairly loose)
365	374	Brown Clay
374	390	Brown Gray & Yellow Clay with brown rock
		(hard)

## **RECEIVED**

AUG 2 3 1979

DIVISION OF ENVIRONMENT OF & EG SEC.