

Distance and direction from nearest town or city street address of well if located within city?
From south side of Lakin - 1 Mile South, 1/4 Mile East, 6 Miles South, 2-3/4 Miles East, 1 1/4 Miles South, 6,910 Ft. North & 3,285 Ft. West

2
WATER WELL OWNER:
Fletcher Ranch, Inc.
RR#, St. Address, Box # :
P. O. Drawer C
City, State, ZIP Code :
Lakin, Kansas 67860
Well #4
Board of Agriculture, Division of Water Resources
Application Number:
20,360

3
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4
DEPTH OF COMPLETED WELL: 405 ft. ELEVATION:
Depth(s) Groundwater Encountered 1. . ft. 2. . ft. 3. . ft.
WELL'S STATIC WATER LEVEL 135 ft. below land surface measured on mo/day/yr 5-17-96
Pump test data: Well water was . ft. after . hours pumping gpm
Est. Yield gpm: Well water was . ft. after . hours pumping gpm
Bore Hole Diameter 30 in. to 405 ft., and . in. to . ft.
WELL WATER TO BE USED AS:
5 Public water supply
8 Air conditioning
11 Injection well
1 Domestic
3 Feedlot
6 Oil field water supply
9 Dewatering
12 Other (Specify below)
2 Irrigation
4 Industrial
7 Lawn and garden only
10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes. . No. X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes No X

5
TYPE OF BLANK CASING USED:
1 Steel
2 PVC
3 RMP (SR)
4 ABS
5 Wrought iron
6 Asbestos-Cement
7 Fiberglass
8 Concrete tile
9 Other (specify below)
CASING JOINTS: Glued . Clamped . Welded X Threaded .
Blank casing diameter .16 in. to .200 ft., Dia . in. to . ft., Dia . in. to . ft.
Casing height above land surface .12 in., weight .42.05 lbs./ft. Wall thickness or gauge No. .250
TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel
2 Brass
3 Stainless steel
4 Galvanized steel
5 Fiberglass
6 Concrete tile
7 PVC
8 RMP (SR)
9 ABS
10 Asbestos-cement
11 Other (specify)
12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot
2 Louvered shutter
3 Mill slot
4 Key punched
5 Gauzed wrapped
6 Wire wrapped
7 Torch cut
8 Saw cut
9 Drilled holes
10 Other (specify)
11 None (open hole)
SCREEN-PERFORATED INTERVALS: From .200 ft. to .405 ft., From . ft. to . ft., From . ft. to . ft.
GRAVEL PACK INTERVALS: From .20 ft. to .405 ft., From . ft. to . ft., From . ft. to . ft.

6
GROUT MATERIAL:
1 Neat cement
2 Cement grout
3 Bentonite
4 Other
Grout Intervals: From .0 ft. to .20 ft., From . ft. to . ft., From . ft. to . ft.
What is the nearest source of possible contamination:
1 Septic tank
2 Sewer lines
3 Watertight sewer lines
4 Lateral lines
5 Cess pool
6 Seepage pit
7 Pit privy
8 Sewage lagoon
9 Feedyard
10 Livestock pens
11 Fuel storage
12 Fertilizer storage
13 Insecticide storage
14 Abandoned water well
15 Oil well/Gas well
16 Other (specify below)
Direction from well?
How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
		See attached log			

7
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-17-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/yr) 5-20-96 under the business name of Minter-Wilson Drilling Co., Inc. by (signature) Nora Keller

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.