


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County Kearny County	Eraction NW 1/4 SE 1/4 SE 1/4	Section number 14	Township number T 26 S R 36	Range number 36
2. Distance and direction from nearest town or city: on Hiway 25, 7 3/4 East, 1 1/2 North, Offset 300' South			3. Owner of well: Walter Fletcher Lakin, KS 67860		
Locate with "X" in section below: 			Sketch map:		
5. Type and color of material			From	To	6. Bore hole dia. 26 in. Completion date 3-28-79 Well depth 326 ft.
Casing Schedule					7. Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary
0 - 145 Plain					8. Use: Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other
145 - 170 Perf.					9. Casing: Material Steel Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 1 ft. in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 36.87 lbs./ft.
170 - 190 Screen					Dia. 16 in. to 326 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. .219
190 - 230 Plain					10. Screen: Manufacturer's name Johnson
230 - 240 Perf.					Type Johnson Galv. Dia. 100-16"
240 - 260 Screen					Slot/gauze <input type="checkbox"/> Length <input type="checkbox"/> Set between <input type="checkbox"/> ft. and <input type="checkbox"/> ft.
260 - 326 Perf.					<input type="checkbox"/> ft. and <input type="checkbox"/> ft. Gravel pack? yes Size range of material 1/4 to 5/8
					11. Static water level: <input type="checkbox"/> mo./day/yr. 77 ft. below land surface Date 2-17-79
					12. Pumping level below land surfaces: 190 ft. after 2 hrs. pumping 1100 g.p.m. 220 ft. after 4 hrs. pumping 1300 g.p.m. Estimated maximum yield 1300 g.p.m.
					13. Water sample submitted: <input type="checkbox"/> mo./day/yr. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date <input type="checkbox"/>
					14. Well head completion: <input type="checkbox"/> Pitless adapter 1 ft. Inches above grade
					15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.
					16. Nearest source of possible contamination: ft. <input type="checkbox"/> Direction N/A Type <input type="checkbox"/> Well disinfected upon completion? <input type="checkbox"/> Yes <input type="checkbox"/> No
					17. Pump: <input type="checkbox"/> Not installed Manufacturer's name Gould 5 stg. 12" Bowl Model number <input type="checkbox"/> HP 125 Volts <input type="checkbox"/> Length of drop pipe 260 ft. capacity 1000 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other
18. Elevation:			20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter Wilson Drilling Co. 208 Business name License No. 67846 Address Box A, Garden City, KS Authorized representative M. Wilson Date 3/17/79		
19. Remarks:					

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

WALTER WILSON DRILLING CO.
INCORPORATED

and Domestic
Water Systems
Complete Installation
and Repairing

Phone 276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

January 23, 1979

Walter Fletcher
Kearny County

Location: S. E. $\frac{1}{4}$ 14-26-36 offset 300' South

Static Water Level - 100

Test #A

	18	Top Soil Fine Sand
18	21	Brown Clay
21	50	Fine to med. sand and gravel
50	83	Med. coarse gravel
83	92	Brown Sandy Clay
92	124	Blue Clay
124	136	Fine to med. sand and gravel (loose)
136	145	Brown Sandy Clay
145	160	Fine to med. sand and gravel (loose)
160	190	Fine to med. sand and gravel 10% Clay (loose)
190	195	Blue Clay and gravel streak
195	215	Blue Clay
215	228	Brown Sandy Clay
228	237	Fine to med. sand and fine gravel (loose)
237	241	Brown Sandy Clay
2	262	Fine to med. sand and gravel (loose)
262	278	Brown Sandy Clay small gravel streak hard
278	293	Brown Sandy Clay
293	322	Brown Sandy Clay White Rock hard
322	329	Fine to med. sand and fine gravel (loose)
329	354	Brown Sandy Clay
354	358	Brown Sandy Clay Brown Brown Rock hard
358	365	Yellow Clay (hard)

RECEIVED

AUG 23 1979

DIVISION OF ENVIRONMENT
OF & EG SEC.