


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County Kearny Co.	Fraction $\frac{1}{4}$ NE $\frac{1}{4}$	Section number 20	Township number 26 S.	Range number 36 E/W
2. Distance and direction from nearest town or city: 7 miles South of Lakin on Hwy 25 3/4 mile East 3 mile South 1 3/4 mile East			3. Owner of well: Earl Berlier R.R. or street: City, state, zip code: Lakin, Kansas 67860		
4. Locate with "X" in section below: 			Sketch map: 6. Bore hole dia. 26 in. Completion date 6-30-78 Well depth 373 ft.		
5. Type and color of material			7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
			8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
			9. Casing: Material Steel Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 1 ft. in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 36.87 lbs./ft. Dia. 26 in. to 373 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 219		
			10. Screen: Manufacturer's name Johnson Type Johnson Galv. 100 16" Slot/gauze 130-320 Perf length Set between 320-340 Screen ft. 340-373 Perf ft. Gravel pack? yes Size range of material 1/4 to 5/8		
			11. Static water level: <input type="checkbox"/> mo./day/yr. 165 ft. below land surface Date 4-28-78		
			12. Pumping level below land surfaces: 171 ft. after 2 hrs. pumping 1000 g.p.m. 175 ft. after 2 hrs. pumping 1600 g.p.m. Estimated maximum yield 1600 g.p.m.		
			13. Water sample submitted: <input type="checkbox"/> mo./day/yr. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date		
			14. Well head completion: <input type="checkbox"/> Pitless adapter 1 ft. inches above grade		
			15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.		
			16. Nearest source of possible contamination: ft. <input type="checkbox"/> Direction NA Type <input type="checkbox"/> Well disinfected upon completion? <input type="checkbox"/> Yes <input type="checkbox"/> No		
			17. Pump: <input type="checkbox"/> Not installed Manufacturer's name Goulds - 5 stage 12" Model number JHC HP 125 Volts Length of drop pipe 220 ft. capacity 800 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
(Use a second sheet if needed)					
18. Elevation: Topography: <input checked="" type="checkbox"/> Hill <input type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley	19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter-Wilson Drlg. 208 Business name License No. Address Box A, Garden City, KS Signed Dane Degees Date 6-9-78 Authorized representative		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

*The
Professionals*

MINTER-WILSON DRILLING CO.
INCORPORATED

Irrigation
and Domestic
Water Systems
Complete Installation
and Repairing

Phone 276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

**EARL BERLIER
KEARNY COUNTY
3/20/78**

Location: NE 20-26-36

Static Water Level- 84'

#3 Pivot

0	53	Sand
53	74	Sand and clay
74	143	Med. to coarse gravel (Loose)
143	149	Brown c
149	155	Med. to coarse gravel (Loose)
155	192	Fine to med. sand and gravel streaks of coarse gravel (Loose)
192	208	Brown clay
208	219	Blue clay
219	286	Fine to med. sand and gravel streaks of coarse gravel (Loose)
286	293	Brown clay (Tight)
293	345	Fine to med. sand and gravel streaks of coarse gravel (Loose)
345	353	Brown clay
353	393	Fine to med. sand and gravel (Loose)
373	391	Brown seek gray and yellow clay (Tight)
391	395	Shale (Hard)

T.D. 373
130 plain
190 perf
20 screen
33 perf