USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County	Fraction		Section number	Township number Range number
. Location of well:	Kearny County	1/4	SW 1/4	21	T 26 S. S R 36 . E/W
Distance and dire	ction from nearest town or city: 7	ile South of	3. 0	Owner of well: Ear	
akin on hi	way 25 3/4 East 4	mile South 2	74 R.R	. or street:	
reet address of well	location if in city:		City	, state, zip code:	Lakin, Kansas 67860
Locate with "X" i		Sketch map:	•		6. Bore hole dia. 26 in. Completion date 6-30-78 Well depth 415 ft.
NW	I I				7 Cable tool Rotary Driven Dug Hollow rod Jetted Bored X Reverse rotary
	!				8. Use: Domestic Public supply Industry
w i	E				X Irrigation Air conditioning Stock Lawn Oil field water Other
**	SE				9. Casing: Material Stee Height: Above or below
	i				Threaded Welded Surface in. RMP PVC Weight
S 1 M	ile ————				Dia 16 in. to 415 ft. depth Wall Thickness: inches or
Type and color of	1.			From To	Dia in. to ft. depth gage No219
			····		10. Screen: Manufacturer's name
					Type Johnson Calv pl00 16" Slot/gauze 300-390 Perf 390-410 Screen
					Stot/gauze 300-390 Perford 390-410 Screen
· National Advantage of the Control					ft.
					Gravel pack? Size range of material
					11. Static water level: mo./day/yr. 190 ft. below land surface Date 5-2-78
					12. Pumping level below land surfaces:
					198 ft. after 2 hrs. pumping 900 g.p.m. 203 ft. after 2 hrs. pumping 1550 g.p.m.
-					Estimated maximum yield 1550 g.p.m.
					13. Water sample submitted: mo./day/yr.
					Yes Y No Date
					14. Well head completion: Pitless adapter 1 ft-Inches above grade
10					With: Neat cement Bentonite Concrete
	Market William Co. Co.				Depth: From ft. to ft.
					16. Nearest source of possible contamination:
					ft Direction Type Well disinfected upon completion? Yes No
					17. Pump: Not installed
					Manufacturer's name Gould - 5 Stage 12"
					Model number JHC HP 125 Volts Length of drop pipe 240 ft. capacity 800 g.p.m.
	5-41-M5				Type:
					Submersible Turbine Reciprocating
	(Use a second	sheet if needed)			Centrifugal Other
3. Elevation:	19. Remarks:				20. Water well contractor's certification: This well was drilled under my jurisdiction and this report
an agrar b					is true to the best of my knowledge and belief.
opography: X Hill					Minter-Wilson Drls. 208 Business name License No.
Slope					Address Box A, Garden City, KS
Upland					Signed Authorized representative
Valley					, construct top/profigurero

And Demestic Action on DRILLING CO. His Properties on Demestic Action on Demestic Action on Properties on DRILLING CO. His Properties on DRILLING CO. His Properties on DRILLING CO. His Properties on DRILLING CO.

Phone 276-8258 . P.O. Box A . GARDEN CITY, KANSAS 67646

April 12, 1978

Earl Berlier Kearny County

Location: S. W. 21-26-36 Static Water Level-190

Pivot #

0	67	Sand
67	102	Brown Clay and Sand
102	215	Med. to coarse gravel (loose)
215	238	Fine to med. sand and gravel streaks of
		coarse gravel (loose)
238	298	Blue Clay
298	365	Fine to med. sand and gravel (loose)
365	415	Fine to med. sand and gravel streaks of
		coarse gravel (loose)
415	428	Brown Sandy Clay (tight)
428	440	Brown Gray Yellow and Red Clay (hard)

T. D. 415