


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Kearny County	Fraction 1/4 NE 1/4	Section number 21	Township number T 26 S. S	Range number R 36 E. E/W
2. Distance and direction from nearest town or city: 7 mile South of Lakin on Highway 25 3/4 mile East 3 mile South Street address of well location if in city: 2 3/4 mile East				3. Owner of well: Earl Berlier R.R. or street: City, state, zip code: Lakin, Kansas 67860		
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 26 in. Completion date 6-30-78 Well depth 308 ft.		
				7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
5. Type and color of material		From		To		8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other
						9. Casing: Material Steel Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 1 ft. in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 36.87 lbs./ft. Dia. 16 in. to 308 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 219
						10. Screen: Manufacturer's name Johnson Type Johnson Galv. 100 16" Slot/gauze 160-280 Perf Set between 280-300 ft. and 300-308 ft. Gravel pack? yes Size range of material 1/4 to 5/8
						11. Static water level: <input type="checkbox"/> mo./day/yr. 103 ft. below land surface Date 4-28-78
						12. Pumping level below land surfaces: 111 ft. after 2 hrs. pumping 1150 g.p.m. 129 ft. after 2 hrs. pumping 1900 g.p.m. Estimated maximum yield 1900 g.p.m.
						13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date <input type="checkbox"/>
						14. Well head completion: <input type="checkbox"/> Pitless adapter 1 ft. Inches above grade
						15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.
						16. Nearest source of possible contamination: ft. <input type="checkbox"/> Direction N/A Type <input type="checkbox"/> Well disinfected upon completion? <input type="checkbox"/> Yes <input type="checkbox"/> No
						17. Pump: <input type="checkbox"/> Not installed Manufacturer's name Could 5 stage 12" Model number JHC HP 125 Volts <input type="checkbox"/> Length of drop pipe 160 ft. capacity 800 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other
18. Elevation:		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter-Wilson Drlg. 208 Business name Box A, Garden City, KS License No. CNE Address Box A, Garden City, KS Date 4-28-78 <i>[Signature]</i> Authorized representative		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

The
Professionals

MINTER-WILSON DRILLING CO.
INCORPORATED

Irrigation
and Domestic
Water Systems
Complete Installation
and Repairing

Phone 276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

EARL BERLIER

KEARNY COUNTY

3/16/78

Location: NE 21-26-36

Static Water Level- 84'

Pivot

0	35	Sand
35	62	Med. to coarse gravel (Loose)
62	70	Brown clay
70	89	Med. to coarse gravel (Loose)
89	114	Brown clay
114	135	Fine to med. sand and gravel (Loose)
135	160	Brown clay
160	181	Fine to med. sand and gravel (Loose)
181	187	Fine to med. sand and gravel 30% clay (Loose)
187	200	Fine to med. sand and gravel (Loose)
200	209	Blue clay 30% gravel
209	273	Fine to med. sand and gravel (Loose)
273	278	Brown clay
278	290	Fine to med. sand and gravel (Loose)
290	308	Fine to med. sand and gravel 10% clay (Loose)
308	335	Brown clay (Tight)
335	347	Brown rock and 30% brown clay (tight) (Hard streaks)
347	374	Brown gray yellow and red clay (Hard)
374	380	Shale (Hard)