


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Kearny County	Fraction 1/4 NE 1/4	Section number 21	Township number T 26 S. S R	Range number 36 E/W
2. Distance and direction from nearest town or city: 7 miles South of Lakin on Hiway 25 3/4 mile East 3 mile South Street address of well location if in city: 2 1/2 mile East				3. Owner of well: Earl Berlier R.R. or street: City, state, zip code: Lakin, Kansas 67860		
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 26 in. Completion date 6-30-78 Well depth 340 ft.		
				7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
5. Type and color of material		From	To	8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
				9. Casing: Material Steel Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 1 ft. in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 36.87 lbs./ft. Dia. 16 in. to 340 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 219		
				10. Screen: Manufacturer's name Johnson Type Johnson Galv. 100 16" Slot/gauze 140-300 Perf Length Set between 300-320 ft. and 320-340 ft. Screen Gravel pack? yes Size range of material 4 to 5/8		
				11. Static water level: <input type="checkbox"/> mo./day/yr. 140 ft. below land surface Date 4-28-78		
				12. Pumping level below land surfaces: 147 ft. after 2 hrs. pumping 1200 g.p.m. 151 ft. after 2 hrs. pumping 1800 g.p.m. Estimated maximum yield 1800 g.p.m.		
				13. Water sample submitted: <input type="checkbox"/> mo./day/yr. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date		
				14. Well head completion: <input type="checkbox"/> Pitless adapter 1 ft. inches above grade		
				15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.		
				16. Nearest source of possible contamination: ft. <input type="checkbox"/> Direction N/A Type <input type="checkbox"/> Well disinfected upon completion? <input type="checkbox"/> Yes <input type="checkbox"/> No		
				17. Pump: <input type="checkbox"/> Not installed Manufacturer's name Goolds - 5 stage 12" Model number JHC HP 125 Volts Length of drop pipe 200 ft. capacity 800 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
18. Elevation:		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter-Wilson Drlg. 208 Business name License No. Address Box A, Cardon City, KS Signed M. Minter-Wilson Date 5-9-78 Authorized representative		
Topography: <input checked="" type="checkbox"/> Hill <input type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley						

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

The Professionals

MINTER-WILSON DRILLING CO.
INCORPORATED

Investigation
and Domestic
Water Systems
Complete Installation
and Repairing

Phone 276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67840

EARL BERLIER
KEARNY COUNTY
3/17/78

Location: NW 21-26-36

Static Water Level- 84'

#2 Pivot

0	43	Sand
43	67	Brown clay
67	121	Med. to coarse gravel (Loose)
121	125	Brown clay
125	131	Med. to coarse gravel (Loose)
131	140	Brown clay
140	153	Fine to med. sand and gravel streak of coarse gravel (Loose)
153	165	Brown clay
165	185	Fine to med.s and and gravel (Loose)
185	190	Brown clay
190	264	Fine to med. sand and gravel (Loose) streaks of coarse gravel
264	269	Brown clay 30% gravel (Loose)
269	327	Fine to med. sand and gravel (Loose) streaks of coarse gravel
327	335	Brwon clay (Tight)
335	339	Fine to med. sand and gravel (Loose)
339	350	Brown clay
350	381	Brown gray and yellow clay with brown rock (Hard)
381	390	Shale (Hard)
		T.D. 340
		140 plain
		160 perf
		20 screen
		20 perf