

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County KEARNY	Fraction SE 1/4 NW 1/4 SE 1/4	Section number 33	Township number T 26 S R 36	Range number 1/W
2. Distance and direction from nearest town or city: county line 6 east 1/4 north 1/4 west Street address of well location if in city:			3. Owner of well: Brad Tate R.R. or street: Lakin, KS 67860 City, state, zip code:			
4. Locate with "X" in section below: N W E S 1 Mile Sketch map: 			6. Bore hole dia. 26 in. Completion date 5-31-76 Well depth 430 ft.			
5. Type and color of material			7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary			
			8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other			
			9. Casing: Material steel Height: 12 ft. Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 36.87 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 36.87 lbs./ft. Dia. 16 in. to 431 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 219 msc			
			10. Screen: Manufacturer's name Johnson Division Type Galv Dia. 16 Slot/gauze 100 Length 20' Set between 380 ft. and 400 ft. Perf. 120-380 ft. and 400-430 ft. Gravel pack? Yes Size range of material 1/2" Down			
			11. Static water level: 176 ft. below land surface Date 5-7-76 12. Pumping level below land surfaces: 183 ft. after 3 hrs. pumping 1500 g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 1500 g.p.m.			
(Use a second sheet if needed)			13. Water sample submitted: Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date			
			14. Well head completion: <input type="checkbox"/> Pitless adapter 17 inches above grade			
			15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.			
			16. Nearest source of possible contamination: N/A ft. Direction Type Well disinfected upon completion? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>			
			17. Pump: Not installed Manufacturer's name Goulds US Pumps Model number 12 JHC HP 200 Volts Length of drop pipe 200 ft. capacity 1000 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other			
18. Elevation: Topography: <input type="checkbox"/> Hill <input checked="" type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley	19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter Wilson Drilling 208 Business name License No. Address P.O. Box A Garden City, KS Signed [Signature] Date 7-1-76 Authorized representative			

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5