WATER WELL RECORD	Form WW(		Divisio	n of Wate	r Resources; App. No. [	20,300	
1 LOCATION OF WATER WELL: County: Kearny	Fraction NE/NE	Lot 1	Section N	umber	Township Number T <b>26</b> S	Range Number R 36 EW	
Distance and direction from nearest town or	city street address of v		Global Pos	sitioning	Systems (decimal deg		
located within city? Lakin S Side-1 M.							
6 M. S. to Parallel RD, 2-3/4 M.E. 2 WATER WELL OWNER: Fletcher I		6 Ft N	Longitud	le:			
RR#, St. Address, Box # : Drawer C		5 Ft W	Elevation Datum:	1:			
City, State, ZIP Code : Lakin, KS		J 10 "	Datum: Data Col	laction	Mathad:		
3 LOCATE WELL'S 4 DEPTH OF COM		40			Memou.		
LOCATION	REETED WEEE		·				
WITH AN "X" IN Depth(s) Groundwate	er Encountered (1)		ft.	(2)	ft. (3).	ft.	
SECTION BOX: WELL'S STATIC W	WELL'S STATIC WATER LEVEL 203 ft. below land surface measured on mo/day/yr3-20-09  Pump test data: Well water was						
F 4 X' 13	ta: Well water was		ft. after		hours pumping	gpm	
WELL WATER TO	m: Well water was				nours pumping.		
			pply			ther (Specify below)	
						······	
SW   SE					<b>v</b>		
Was a chemical/bacte							
"	d	Wate	r well disii	ntected?	Yes No	••••	
S S S S S S S S S S S S S S S S S S S				G A GD II	C TOD THE CL. 1	<u> </u>	
5 TYPE OF CASING USED: 5 Wrough 1 Steel 3 RMP (SR) 6 Asbesto		icrete tile er (specify		CASIN	G JOINTS: Glued	Clamped	
2 PVC 4 ABS 7 Fibergla							
Blank casing diameter 16 in. to 24		i	n. to	ft.,	Diameter	in. toft.	
Casing height above land surface12	in., Weight						
TYPE OF SCREEN OR PERFORATION MAT							
1) Steel 3 Stainless Steel 5 Fiber 2 Brass 4 Galvanized Steal 6 Cor	erglass 7 PVC		ABS		11 Other (Specify)		
SCREEN OR PERFORATION OPENINGS AR	,	K) 10 A	Asbestos-C	ement	12 None used (oper	i noie)	
1 Continuous slot 3 Mill slot 5		Torch cut	9 Drille	ed holes	11 None (open l	nole)	
2 Louvered shutter 4 Key punched 6	Wire wrapped 8	Saw cut	10 Other	r (specify	/)	******************	
SCREEN-PERFORATED INTERVALS: From	<b>240</b> ft. to	405	ft.,	From	ft. to	ft.	
From GRAVEL PACK INTERVALS: From	ft. to	170	ft.,	From	ft. to	ft.	
	ft. to						
	_		· ·				
6 GROUT MATERIAL: 1 Neat cement	Cement grout 3 B	entonite	4 Other	20			
Grout Intervals: From ft. to What is the nearest source of possible contamina		17.0	It. to	t	t., From	ft. toft.	
1 Septic tank 4 Lateral lines		10 Livesta	ock nens	13 Inc	secticide storage	16 Other (specify	
						below)	
3 Watertight sewer lines 6 Seepage pit	9 Feedyard		zer storage			•••••	
Direction from well?					N/A		
FROM TO LITHOLOGI	C LOG	FROM	TO		PLUGGING INT	ERVALS	
See attached log	•						
Sec accaence 108	<u> </u>					·	
						F19 (III ) III	
7 CONTRACTOR'S OR LANDOWNER'S O	EDTIFICATION.	This water	well was	1) bonst	nucted (2) reconstruct	ted or (2) plugged	
under my jurisdiction and was completed on (mo							
Kansas Water Well Contractor's License No							
under the business name of Minter-Wilson	Drilling Co.,	Inc. by	y (signatur	re) Hora	n) Rellen		
INSTRUCTIONS: Use typewriter or ball point pen. PLE	ASE PRESS FIRMLY and	PRINT clear	ly. Please fil	ll in blanks	s, underline or circle the c		
three copies to Kansas Department of Health and Environm 785-296-5522. Send one to WATER WELL OW							
http://www.kdheks.gov/waterwell/index.html.		,					

## The Professionals MINTER-WILSON DRILLING CO. Unrigation and Domestic Water Systems Complete Installation

and Repairing

## **INCORPORATED**

Phone 620-276-8269 P.O. Box A • **GARDEN CITY, KANSAS 67846** 

NAME

FLETCHER RANCH - CIRCLE #7

COUNTY

**KEARNY** 

DATE

12-17-08

LOCATION:

NE 1/4 1-26-36 - NORTHEAST CORNER OF CIRCLE

STATIC WATER LEVEL - APPROX 200 FT.

## TEST #2

0' TO 1' - TOP SOIL

4' - BROWN CLAY 1' TO

4' TO 18' - BROWN SANDY CLAY

18' TO 48' - FINE TO MEDIUM SAND & GRAVEL WITH CLAY STREAKS

48' TO 107' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE - 10% CLAY

107' TO 117' - BROWN & BLUE CLAY

117' TO 208' - BLUE CLAY

208' TO 219' - BROWN CLAY

219' TO 229' - FINE TO MEDIUM SAND & GRAVEL

229' TO 234' - BROWN CLAY

234' TO 240' - FINE TO MEDIUM SAND & GRAVEL

240' TO 247' - FINE TO MEDIUM SAND & GRAVEL WITH CLAY STREAKS

247' TO 289' - BROWN CLAY

289' TO 308' - BROWN SANDY CLAY

308' TO 344' - BROWN CLAY

344' TO 353' - FINE TO MEDIUM SAND

353' TO 368' - BROWN CLAY

368' TO 387' - FINE TO MEDIUM SAND & FINE GRAVEL

387' TO 391' - BROWN CLAY

391' TO 395' - BROWN CLAY WITH BROWN ROCK 30%

395' TO 408' - BROWN YELLOW RED CLAY - HARD PULL DOWN

408' TO 455' - SHALE - HARD PULL DOWN