WATER WELL RECORD	Form WWC-5	Division of Water	r Resources App. No	21,546
1 LOCATION OF WATER WELL:	Fraction	Section Number		Range Number
County: KEARNY	14 NE 14 NW 14 SE 14	2	T 26 S	R 36 □E 🗹 W
Street/Rural Address of Well Location;	if unknown, distance & direction	Global Positioning		
from nearest town or intersection: If at owner's address, check here .		Latitude: (in decimal degrees)		
S SIDE OF LAKIN-1 M S, 1/4 M E, 6 M S,1-3/4 M E,		Longitude: (in decimal degrees)		
1-1/3RD M S, 2,260 FT. N & 1,900 FT. W		Elevation:		
2 WATER WELL OWNER: AMERICAN IMPLEMENT		Datum: WGS 84, NAD 83, NAD 27		
RR#, Street Address, Box #: PO BOX 855		Collection Method: GPS unit (Make/Model:)		
0'4 0'44 770 0 1		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey		
GARDE	N CITY, KS 67846	Est. Accuracy:		
3 LOCATE WELL				
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 395 ft.				
SECTION BOX: Depth(s) Groundwater Encountered (1)				
SECTION BOX: N Depth(s) Groundwater Encountered (1)				
Pump test data: Well water wasft. after hours pumping gpm				
EST. YIELDgpm. Well water wasft. after				
w E Bore Hole Diameter 30 in. to 395 ft., and in. to ft.				
WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well				
swse Domestic Feedlot Oil field water supply Dewatering Other (Specify below)				
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well				
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ✓ No				
S If yes, mo/day/yr sample was submitted 1 mile Water well disinfected?				
water wen dishi				
5 TYPE OF CASING USED: Steel PVC Other				
CASING JOINTS: Glued Clamped Welded Threaded				
Casing diameter16 in. to .250.	ft., Diameter in. t	o ft., D	iameter	. in. to ft.
Casing height above land surface				
TYPE OF SCREEN OR PERFORATION MATERIAL:				
✓ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify) ☐ Brass ☐ Galvanized Steel ☐ None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:				
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)				
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)				
SCREEN-PERFORATED INTERVALS: From 250 ft. to 395 ft., From ft. to ft.				
From ft. to ft., From ft. to ft.				
GRAVEL PACK INTERVALS: From 20 ft. to 175 ft., From 235 ft. to 395 ft.				
	From ft. to			
6 GROUT MATERIAL: Neat ceme	ent Cement grout Benton	ite		
	20 ft., From 175	t. to .235 ft.,	From	. ft. toft.
What is the nearest source of possible conta	_	—		
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well				
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well				
Direction from well				
FROM TO LITHOLOG				GGING INTERVALS
			<u></u>	
SEE ATTACHED LOG				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged				
under my jurisdiction and was completed on (mo/day/year) 5-9-09 and this record is true to the best of my knowledge and belief.				
Kansas Water Well Contractor's License No 208 This Water Well Record was completed on (mo/day/year) 5-11-09				
under the business name of MINTER-WILSON DRLG, CO., INC. by (signature) May Heller				
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three conies				
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.				
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.				
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy				

Irrigation and Repairing

INCORPORATED

P.O. Box A • **GARDEN CITY, KANSAS 67846** Phone 620-276-8269

NAME

BRENT TOKOI

COUNTY

KEARNY

DATE

12-15-08

LOCATION:

SE 1/4 2-26-36 - CIRCLE # T16 - LAKIN LANE & PARALLEL ROAD

2-1/2 MILES EAST, 7/8THS OF A MILE SOUTH & 1/8TH OF A MILE EAST - SW EDGE OF CIRCLE

STATIC WATER LEVEL - 200 FT.

TEST #1

0' TO 16' - FINE SAND

16' TO 23' - BROWN SANDY CLAY

23' TO 116' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

116' TO 119' - BROWN CLAY

119' TO 174' - FINE TO MEDIUM SAND & GRAVEL WITH STREAKS OF **BROWN CLAY**

174' TO 180' - BROWN CLAY

180' TO 186' - BLUE CLAY

186' TO 214' - FINE TO MEDIUM SAND & GRAVEL

214' TO 236' - BROWN SANDY CLAY WITH STREAKS OF GRAVEL

236' TO 239' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

239' TO 250' - BROWN SANDY CLAY

250' TO 263' - FINE TO MEDIUM SAND & GRAVEL

263' TO 265' - BROWN SANDY CLAY

265' TO 276' - FINE TO MEDIUM SAND & GRAVEL WITH STREAKS OF **BROWN CLAY**

276' TO 279' - BROWN SANDY CLAY

279' TO 283' - FINE TO MEDIUM SAND & GRAVEL

283' TO 296' - BROWN SANDY CLAY WITH STREAKS OF SAND

296' TO 305' - BROWN SANDY CLAY WITH STREAKS OF HARD WHITE CLAY

305' TO 349' - BROWN SANDY CLAY

349' TO 361' - FINE TO MEDIUM SAND & GRAVEL

361' TO 380' - BROWN ROCK & FINE SAND WITH LAYERS OF YELLOW CLAY 80% SAND GRAVEL

380' TO 400' - YELLOW CLAY WITH STREAKS OF BROWN ROCK & SAND

400' TO 417' - HARD BROWN CLAY WITH STREAKS OF BROWN ROCK **400 PULL DOWN**

417' TO 425' - RED & BROWN CLAY LAYERED - 600 PULL DOWN

425' TO 435' - HARD BROWN CLAY & BROWN ROCK 10%

435' TO 465' - HARD BROWN CLAY WITH 20% BROWN ROCK

465' TO 500' - SHALE