WATER WELL RECORD		Form W	WC-5	Division of Wate	r Resources App. No	0.	
1 LOCATION QF WATER WELL:		Fraction		Section Number			
County: Kearny Street/Rural Address of Well Location; i		1/4 NE1/4 N	e 1/4 SE 1/4			R 36 □E 🐠	
		Global Positioning					
from nearest town or intersection: If at owner's address, check here 3 .				Latitude:			
Lakin, Ks. 67860				Longitude:			
-				Datum: WGS 84, NAD 83, NAD 27			
2 WATER WELL OWNER: David Gugel meyer RR#, Street Address, Box #: 35 Lakin Lane				Collection Method:			
				GPS unit (Make/Model:)			
Lakin, Ks. 67860			☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m				
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 375 ft.							
WITH AN "X" IN							
SECTION BOX:							
111	WELL'S STATIC WATER LEVEL						
	FST VIFI D onm Well water was ft after hours numping onm						
W NW NE	EST. YIELDgpm Well water wasft. afterhours pumpinggpm Bore Hole Diameterft., andft.						
	WELL WATER TO BE USED AS: Public water supply Geothermal Injection wall						
Domestic							
Irrigation Industrial Domestic-lawn & garden Monitoring well							
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No							
S If yes, mo/day/yr sample was submitted							
water win districted: A 1 cs 1 no							
5 TYPE OF CASING USED: Steel PVC Other							
CASING JOINTS: Glued Clamped Welded Threaded							
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter in. to 375 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface in., Weight Solution in., Weight Wall thickness or gauge No. 508.							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
Steel Stainless Steel YPVC Other (Specify)							
Brass Galvanized Steel None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole) Louvered shutter Key punched Wire wrapped Saw cut Other (specify)							
SCREEN-PERFORATED INTERVALS: From 225 ft. to 375 ft., From ft. to ft.							
From							
GRAVEL PACK INTERVALS: From 4% ft. to 3% ft., From ft. to ft.							
From							
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other							
Grout Intervals: From							
What is the nearest source of possible contamination:							
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well							
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well ☐ Fasture ☐							
Direction from well							
FROM TO	LITHOLOG		FROM	TO LITHO. LO	OG (cont.) <u>or</u> PLU	GGING INTERVALS	
	ndy Topsoil						
2 65 Tar		² 7	-				
_ 1	1. Sand	<u> </u>					
	rse sand +						
	c/ay	2/1 <u>C</u>					
	d. sand						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year)							
under my jurisdiction and was completed on (mo/day/year)							
Kansas Water Well Contractor's License No 533 This Water Well Record was completed on morday year) 5/8/// under the business name of 5 ant cro Water Well Record was completed on morday year) by (signature)							
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and peck the correct answers. Send three copies							
(white, blue, pink) to Kansas I	Department of Health	and Environment, Bureau	of Water, Geol	ogy Section, 1000 SW Jac	ckson St., Suite 420,	Topeka, Kansas 66612-1367.	
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at							
http://www.kdheks.gov/waterwell/index.html. KSA 82a-1212							
120/1 020-1212							