WATER WELL RECORD	Form WW	/C-5	Division of Wate	r Resources App. No	20,361
1 LOCATION OF WATER WELL:	Fraction LOT 2			Township No.	Range Number
County: KEARNY		4 NE 1/4	4	T 26 S	R 36 □E 🗹 W
Street/Rural Address of Well Location; if unknown, distance & direction			Global Positioning System (GPS) information:		
from nearest town or intersection: If at owner's address, check here		Latitude: (in decimal degrees) Longitude: (in decimal degrees)			
S SIDE OF LAKIN-1 M S, 1/4 M E TO LAKIN LANE, 6 M S TO PARALLEL RD, 1/4 M W, 1-1/3RDS M S 6710' N-2590' W		Elevation:			
		<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27			
2 WATER WELL OWNER: FLETCHER RANCH, INC. RR#, Street Address, Box #: PO BOX C		Collection Method: GPS unit (Make/Model:)			
City, State, ZIP Code : LAKIN, KANSAS 67860		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
EARTH, TOTOGO 07000			Est. Accuracy:		
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF	COMPLETED WELL.	435	ft.		
SECTION BOX: Depth(s) Groundwater Encountered (1)					
WELL'S STATIC WATER LEVEL175ft. below land surface measured on mo/day/yr. 4-11-13					
Pump test data: Well water was					
W -NW NE EST. YIELD					
W					
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)					
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No					
S If yes, mo/day/yr sample was submitted					
water went distintected: Tes Las No					
5 TYPE OF CASING USED: Steel PVC Other					
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter					
Casing height above land surface12	in Weight	12.05	lbs./ft Wall thic	kness or gauge No	
Casing height above land surface					
☑ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)					
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:					
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)					
☐ Louvered shutter ☐ Key punched ☑ Wire wrapped ☐ Saw cut ☐ Other (specify)					
SCREEN-PERFORATED INTERVALS: From					
From					
From					
6 GROUT MATERIAL: Neat ceme	ent 🖊 Cement grout	☐ Benton	ite		
Grout Intervals: From0 ft. to	20 ft., From	220 f	t. to .280 ft.,	From	. ft. toft.
What is the nearest source of possible conta					
☐ Septic tank ☐ Lateral lin ☐ Sewer lines ☐ Cesspool		Livestock per Fuel storage			er (specify below)
Watertight sewer lines Seepage r		Fertilizer sto	rage 🔲 Oil well/ga	s well	
Direction from well NORTHWEST					
FROM TO LITHOLOG	IC LOG	FROM	TO LITHO. LO	OG (cont.) or PLU	GGING INTERVALS
SEE ATTACHED LOG				t	
OEE AT TACHED ECC					
7 CONTRACTOR'S OR LANDOWNER	2'S CERTIFICATION:	This water	well was 17 constru	icted reconst	octed or Districted
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was \(\bigcirc \) constructed, \(\bigcirc \) reconstructed, or \(\bigcirc \) plugged under my jurisdiction and was completed on \((\mo/\day/year) \) .4-11-13 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No208 This Water Well Record was completed on (mo/day/year) 4-17-13					
under the business name of .MINTER-WILSON DRILLING CO., INC. by (signature) In Orac. Kellen					
INSTRUCTIONS: Use ty pewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367.					
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well, Vi sit us at					
http://www.kdheks.gov/waterwell/index.html. KSA 82a-1212 Check: White Conv. Blue Conv. Pink Conv.					
NOA 024-1212			Check: Wh	пе Сору, 🔲 ВІи	e Copy, Pink Copy

The Professionals MINTER-WILSON DRILLING CO. Irrigation and Domestic Water Systems Complete Installation

Irrigation and Repairing

INCORPORATED

Phone 620-276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

NAME

WALTER FLETCHER - CIRCLE # 1

COUNTY

KEARNY

DATE

12-20-12

LOCATION:

N 1/2 4-26-36 - 100 FT. SOUTHEAST OF PIVOT

STATIC WATER LEVEL - APPROX. 210 FT.

TEST#1

0' TO 1' - TOP SOIL

1' TO 15' - BROWN SANDY CLAY

15' TO 149' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

149' TO 158' - BROWN & BLUE CLAY

158' TO 178' - BLUE CLAY

178' TO 196' - BROWN CLAY

196' TO 204' - BROWN CLAY WITH GRAVEL STREAK

204' TO 214' - BROWN CLAY

214' TO 231' - FINE TO MEDIUM SAND & GRAVEL

231' TO 260' - BROWN CLAY WITH GRAVEL STREAKS

260' TO 295' - BROWN CLAY

295' TO 300' - FINE TO MEDIUM SAND & GRAVEL

300' TO 344' - BROWN CLAY

344' TO 384' - FINE TO MEDIUM SAND & GRAVEL

384' TO 404' - BROWN CLAY

404' TO 412' - BROWN CLAY WITH 30% BROWN ROCK

412' TO 422' - BROWN ROCK - 30% BROWN CLAY

422' TO 429' - YELLOW CLAY

429' TO 455' - SHALE - 250-300 PULL DOWN - HARD