

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

SE NW SW

1. Location of well:		County Kearny	Fraction SE 1/4 NW 1/4 SW 1/4	Section number 32	Township number T 26	Range number S 37	E 10																																																
2. Distance and direction from nearest town or city: 10 mi. North of Ulysses 1 1/2 mi. West Street address of well location if in city:				3. Owner of well: Carl Waechter R.R. or street: City, state, zip code: Ulysses, Kansas 67880																																																			
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 26 in. Completion date 4/2/76 Well depth 369 ft.																																																			
<div style="text-align: center;"> </div>		C of Gtr.		7. <input checked="" type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary																																																			
5. Type and color of material		<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th style="width:10%;">From</th> <th style="width:10%;">To</th> </tr> </thead> <tbody> <tr><td>Clay</td><td>0</td><td>120</td></tr> <tr><td>Blind (sand streaks)</td><td>120</td><td>160</td></tr> <tr><td>sand & gravel</td><td>160</td><td>200</td></tr> <tr><td>sandy clay & real fine loose sand</td><td>200</td><td>280</td></tr> <tr><td>loose sandstone</td><td>280</td><td>340</td></tr> <tr><td>loose sandstone & hard rock</td><td>340</td><td>368</td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> </tbody> </table>			From	To	Clay	0	120	Blind (sand streaks)	120	160	sand & gravel	160	200	sandy clay & real fine loose sand	200	280	loose sandstone	280	340	loose sandstone & hard rock	340	368																												8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other			
					From	To																																																	
				Clay	0	120																																																	
				Blind (sand streaks)	120	160																																																	
				sand & gravel	160	200																																																	
sandy clay & real fine loose sand	200	280																																																					
loose sandstone	280	340																																																					
loose sandstone & hard rock	340	368																																																					
9. Casing: Material Steel Height: 12 in. Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 368 lb./ft. Dia. 16 in. to 369 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 219																																																							
10. Screen: Manufacturer's name Lakewood Type Millslot Dia. 16 in. Slot/gauze 1/8 x 2 Length 140 Set between 160 ft. and 200 ft. 269 ft. and 369 ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material 1-1																																																							
11. Static water level: 20 ft. below land surface Date 2/17/76 mo./day/yr.																																																							
12. Pumping level below land surfaces: 340 ft. after 10 hrs. pumping 1800 g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 1800 g.p.m.																																																							
13. Water sample submitted: mo./day/yr. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date																																																							
14. Well head completion: <input type="checkbox"/> Pitless adapter <input checked="" type="checkbox"/> 12 inches above grade																																																							
15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.																																																							
16. Nearest source of possible contamination: NA ft. Direction Type Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No																																																							
17. Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name Model number HP Volts Length of drop pipe ft. capacity g.p.m. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other																																																							
18. Elevation:		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. High Plains Drilling & Supply Business name License No. Address 402 N 3rd Garden City, Ka. Signed Bill P. Markson Date 4-27-76 Authorized representative																																																			

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

MI-1023