


1 LOCATION OF WATER WELL: County: SE SE NE NE Section Number: 27 Township Number: 26 Range Number: 4
 Distance and direction from nearest town or city street address of well if located within city? 26011 S. Victory Rd Cheney, KS

2 WATER WELL OWNER: Daniel Dancasse
 RR#, St. Address, Box #: 2518 S. Ellis
 City, State, ZIP Code: Wichita, KS 67216
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  **4 DEPTH OF COMPLETED WELL:** 93 ft. **ELEVATION:** 10-1-97 ft.
 Depth(s) Groundwater Encountered: 30 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 30 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 20 gpm ft. after 11 hours pumping gpm
 Est. Yield 20 gpm: Well water was 93 ft. after 11 hours pumping gpm
 Bore Hole Diameter: 11 in. to 93 ft. and 93 in. to 93 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 1 3 Feedlot 1 6 Oil field water supply 1 9 Dewatering 1 12 Other (Specify below)
 2 Irrigation 1 4 Industrial 1 7 Lawn and garden only 1 10 Monitoring well 1
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel 5 3 RMP (SR) 5 6 Asbestos-Cement 5 8 Concrete tile 5 CASING JOINTS: Glued X Clamped X
 2 PVC 5 4 ABS 5 7 Fiberglass 5 9 Other (specify below) 5 Welded 5
 Blank casing diameter 5 in. to 29 ft. Dia. 2.40 in. to 2.40 ft. Dia. 100 PSI
 Casing height above land surface 29 in. weight 2.40 lbs./ft. Wall thickness or gauge No. 100 PSI
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 5 3 Stainless steel 5 5 Fiberglass 5 8 RMP (SR) 5 10 Asbestos-cement 5
 2 Brass 5 4 Galvanized steel 5 6 Concrete tile 5 9 ABS 5 11 Other (specify) 5
 12 None used (open hole) 5
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 5 3 Mill slot 5 5 Gauzed wrapped 5 8 Saw cut 5 11 None (open hole) 5
 2 Louvered shutter 5 4 Key punched 5 6 Wire wrapped 5 9 Drilled holes 5
 10 Other (specify) 5
 SCREEN-PERFORATED INTERVALS: From 29 ft. to 93 ft. From 29 ft. to 93 ft.
 GRAVEL PACK INTERVALS: From 30 ft. to 93 ft. From 30 ft. to 93 ft.

6 GROUT MATERIAL: 3 Neat cement 30 2 Cement grout 3 Bentonite 4 Other 4
 Grout intervals: From 3 ft. to 30 ft. From 3 ft. to 30 ft. From 3 ft. to 30 ft. From 3 ft. to 30 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 5 4 Lateral lines 5 7 Pit privy 5 10 Livestock pens 5 14 Abandoned water well 5
 2 Sewer lines 5 5 Cess pool 5 8 Sewage lagoon 5 11 Fuel storage 5 15 Oil well/Gas well 5
 3 Watertight sewer lines 5 6 Seepage pit 5 9 Feedyard 5 12 Fertilizer storage 5 16 Other (specify below) 5
 13 Insecticide storage 5
 Direction from well? Northwest How many feet? 200

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	93	all shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-29-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 10-30-97 under the business name of Weninger Drilling Inc. by (signature) Thickule Gorges

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.