

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Reno</u>		<u>SW 1/4 SW 1/4 SE 1/4</u>	<u>11</u>	<u>T 26 S</u>	<u>R 4 EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>1 No of Pretty Prairie 1 1/2 W N.S. side</u>					
2 WATER WELL OWNER: <u>Clair Graber</u>		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # <u>23203 So R17 HW</u>		Application Number: <u>42663</u>			
City, State, ZIP Code <u>Pretty Prairie KS 67570</u>					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>116</u> ft. ELEVATION: <u>9-25-97</u>			
		Depth(s) Groundwater Encountered <u>1 32</u> ft. 2. <u>32</u> ft. 3. <u>32</u> ft.			
		WELL'S STATIC WATER LEVEL <u>32</u> ft. below land surface measured on mo/day/yr <u>9-25-97</u>			
		Pump test data: Well water was <u>NA</u> ft. after <u>NA</u> hours pumping <u>NA</u> gpm			
		Est. Yield <u>NA</u> gpm: Well water was <u>NA</u> ft. after <u>NA</u> hours pumping <u>NA</u> gpm			
		Bore Hole Diameter <u>30</u> in. to <u>116</u> ft. and <u>NA</u> in. to <u>NA</u> ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes <u>NA</u> No <u>X</u> ; If yes, mo/day/yr sample was submitted <u>NA</u>			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued <u>X</u> Clamped <u>NA</u>			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)			
		7 Fiberglass 10 Asbestos-cement			
Blank casing diameter <u>16</u> in. to <u>76</u> ft. Dia <u>NA</u> in. to <u>NA</u> ft.		11 Other (specify) <u>NA</u>			
Casing height above land surface <u>12</u> in. weight <u>55-40</u> lbs./ft. Wall thickness or gauge No. <u>NA</u>		12 None used (open hole)			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify) <u>NA</u>			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 6 Wire wrapped 9 Drilled holes		10 Other (specify) <u>NA</u>			
2 Louvered shutter 4 Key punched 7 Torch cut					
SCREEN-PERFORATED INTERVALS: From <u>76</u> ft. to <u>116</u> ft.					
GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>116</u> ft.					
6 GROUT MATERIAL:		4 Other <u>NA</u>			
1 Neat cement 2 Cement grout 3 Bentonite					
Grout Intervals: From <u>0</u> ft. to <u>20</u> ft.					
What is the nearest source of possible contamination:		14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		16 Other (specify below) <u>NA</u>			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	TS			
3	28	med Sand (Dry)			
28	30	Clay			
30	116	med Sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) <u>reconstructed</u> , or (3) <u>plugged</u> under my jurisdiction and was completed on (mo/day/year) <u>10-1-97</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>537</u> This Water Well Record was completed on (mo/day/year) <u>10-29-97</u> under the business name of <u>Flowers Drilling & Pump</u> by (signature) <u>M. H. Flowers</u>					