

1 LOCATION OF WATER WELL: County: Ben Fraction: SE 1/4 NE 1/4 NE 1/4 Section Number: 13 Township Number: 26S Range Number: 4 E

Distance and direction from nearest town or city street address of well if located within city? 5 West 1/4 S of 61st N. - 23000 S. Rayle

2 WATER WELL OWNER: Dwayne Gorges & Wendy Schmitt Permit # WS4275

RR#, St. Address, Box #: 23400 S. Rayle Board of Agriculture, Division of Water Resources

City, State, ZIP Code: mt. Hope, KS 67108 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 

4 DEPTH OF COMPLETED WELL: 78 ft. ELEVATION: 4-16-98

Depth(s) Groundwater Encountered: 28 ft. below land surface measured on mo/day/yr

WELL'S STATIC WATER LEVEL: 28 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 25 gpm: Well water was 11 in. to 78 ft. and 78 in. to 78 ft.

Est. Yield 25 gpm: Well water was 11 in. to 78 ft. and 78 in. to 78 ft.

Bore Hole Diameter: 11 in. to 78 ft. and 78 in. to 78 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded

Blank casing diameter 5 in. to 38 ft. Dia 2.40 in. to 1600 PSI

Casing height above land surface 12 in. weight 2.40 lbs./ft. Wall thickness or gauge No. 1600 PSI

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes

7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 38 ft. to 78 ft. From 38 ft. to 78 ft. From 38 ft. to 78 ft. From 38 ft. to 78 ft.

GRAVEL PACK INTERVALS: From 28 ft. to 78 ft. From 28 ft. to 78 ft. From 28 ft. to 78 ft. From 28 ft. to 78 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 28 ft. From 28 ft. to 78 ft. From 28 ft. to 78 ft. From 28 ft. to 78 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? East How many feet? 130

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-16-98 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 4-22-98

under the business name of Weninger Drilling Inc. by (signature) Michael Gorges

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.