WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Reno NE 1/4 NE 1/4 SE 1/4 11 Т 26 S R 4W E/W Distance and direction from nearest town or city street address of well if located within city? 22105 Worthington Rd. Mt. Hope, Kansas WATER WELL OWNER: ROBL CONSTRUCTION Board of Agriculture, Division of Water Resource 5842 W. 21st N. RR#,ST. ADDRESS,BOX #: Wichita Kansas CITY, STATE: ZIP CODE Application Number: 130 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: ft. ELEVATION: WITH AN "X" IN SECTION BOX Depth of groundwater Encountered: ft. Ν ft. ft. WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 11/20/15 Well water was NW ΝE Pump test data: ft. after apm Est. Yield: Well water was ft. after hours of pumping @ map ≌ Bore Hole Diameter 12 to 130 and in. ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering SW SE 7. Lawn and garden only 1. Domestic 3. Feedlot 5. Public water supply 12. Other (Specify below) 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO submitted (YES) Was Water Well Disinfected? NO 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: ( Glued Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4 ABS 5 45 Blank casing diameter Dia. in. ft., Dia to in to ft. 12 Casing height above land surface: in. 2.35 Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 1. Steel 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 12. None used (open hole) 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None ( open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 45 130 to From to ft. ft. From to ft.. From to ft. 24 GRAVEL PACK INTERVALS: ft 130 From to ft., From ft to From ft. ft. From **GROUT MATERIALS** Other 6 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From 4 ft. 24 ft. to ft.. From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privv 13. Insecticide storage 15. Oil well/Gas well 4. Lateral lines 1. Septic tank 8. Sewage lagoon 16. Other (specify below) 11. Fuel storage 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line Northwest Direction from well? How many feet? 200 ft. plus То From LITHOLOGIC LOG From To LITHOLOGIC LOG topsoil 20 3 clav 20 clay and fine sand mix 26 26 110 red shale 110 130 grey shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and 11/20/15 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 11/23/15

under the business name of Harp Well and Pump Service by (signature)

Todd S. Harp