


1 LOCATION OF WATER WELL: County: Renov Fraction: SE 1/4 Section Number: 15 Township Number: T 26 S Range Number: R 4 E/W

Distance and direction from nearest town or city street address of well if located within city?  
1/4 W 2 No St Joe KS

2 WATER WELL OWNER: RR#, St. Address, Box #: Blanchigny Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: Hope KS Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 127 ft. ELEVATION: 1245 ft.

Depth(s) Groundwater Encountered 1. 45 ft. 2. 45 ft. 3. 45 ft.  
 WELL'S STATIC WATER LEVEL 45 ft. below land surface measured on mo/day/yr 9-14-91  
 Pump test data: Well water was 45 ft. after 1/2 hours pumping 91 gpm  
 Est. Yield 1 gpm: Well water was 45 ft. after 1/2 hours pumping 91 gpm  
 Bore Hole Diameter 11 in. to 127 ft. and 127 in. to 127 ft.  
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 4 Industrial 7 Lawn and garden only 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 PVC 8 Concrete tile 9 Other (specify below) 10 Asbestos-cement  
 Blank casing diameter 5 in. to 50 ft., Dia. 50 in. to 50 ft., Dia. 50 in. to 50 ft., Dia. 50 in. to 50 ft., Dia.  
 Casing height above land surface 12 in., weight 2.49 lbs./ft. Wall thickness or gauge No. 160 PVC

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 11 None (open hole) 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 50 ft. to 127 ft., From 50 ft. to 127 ft., From 50 ft. to 127 ft., From 50 ft. to 127 ft.  
 GRAVEL PACK INTERVALS: From 23 ft. to 127 ft., From 23 ft. to 127 ft., From 23 ft. to 127 ft., From 23 ft. to 127 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 3 ft. to 23 ft., From 3 ft. to 23 ft., From 3 ft. to 23 ft., From 3 ft. to 23 ft.  
 What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)  
 Direction from well? EAST How many feet? 100

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Clay			
3	127	Charcoal & green & red shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/8 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 9-18-91 under the business name of Blanchigny by (signature) [Signature]