

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: NE Fraction: 1/4 NW 1/4 NE 1/4 Section Number: 24 Township Number: 26 Range Number: 4

Distance and direction from nearest town or city street address of well if located within city: 1 So 4/4 W Andale KS

2 WATER WELL OWNER: GARY Reichenberger Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 1511 E Prairie Rd
City, State, ZIP Code: Mt Hope KS 67108 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 95 ft. ELEVATION: 38 ft.

Depth(s) Groundwater Encountered: 1 38 ft. 2 38 ft. 3 38 ft.

WELL'S STATIC WATER LEVEL: 28 ft. below land surface measured on 12-17-91

Pump test data: Well water was 40 ft. after 12 hours pumping 15 gpm

Est. Yield: 20-30 gpm Well water was 40 ft. after 12 hours pumping 15 gpm

Bore Hole Diameter: 11 in. to 95 ft. and 95 in. to 95 ft.

WELL WATER TO BE USED AS:

5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:

1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X

Blank casing diameter: 5 in. to 22 ft. Dia 22 in. to 22 ft. Dia 22 in. to 22 ft. Dia 22 in. to 22 ft. Dia

Casing height above land surface: 12 in. weight 2-80 lbs./ft. Wall thickness or gauge No 160 PVC

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes

SCREEN-PERFORATED INTERVALS: From 22 ft. to 95 ft. From 22 ft. to 95 ft. From 22 ft. to 95 ft. From 22 ft. to 95 ft.

GRAVEL PACK INTERVALS: From 21 ft. to 95 ft. From 21 ft. to 95 ft. From 21 ft. to 95 ft. From 21 ft. to 95 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 21 ft. From 3 ft. to 21 ft. From 3 ft. to 21 ft. From 3 ft. to 21 ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? SW How many feet? 120

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 2 Top soil

2 12 Clay

12 95 Red & Blue Green shale

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-17-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 12-17-91 under the business name of Weninger Duller by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.