


1 LOCATION OF WATER WELL: County: Reho Fraction: NE 1/4 NE 1/4 SE 1/4 Section Number: 27 Township Number: T 26 S Range Number: R 4 E/W

Distance and direction from nearest town or city street address of well if located within city? See Below (1/2 No. of St. Joe, KS)

2 WATER WELL OWNER: Tina Underwood RR#, St. Address, Box #: 26103 S. Ray Rd. City, State, ZIP Code: Cheney, KS 67025 Board of Agriculture, Division of Water Resources Application Number: 90

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 90 ft. ELEVATION: 45 ft. 1. Depth(s) Groundwater Encountered: 47 ft. 2. WELL'S STATIC WATER LEVEL: 47 ft. below land surface measured on mo/day/yr 5-10-94 Pump test data: Well water was 30 ft. after 1/2 hours pumping 26 gpm Est. Yield: 20 gpm Well water was 90 ft. after 1/2 hours pumping 26 gpm Bore Hole Diameter: 11 in. to 90 ft., and 90 in. to 90 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped Welded Threaded Blank casing diameter: 3 in. to 12 in. Dia. 2.00 in. to 100 PSI lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 30 ft. to 90 ft. From 45 ft. to 90 ft. GRAVEL PACK INTERVALS: From 45 ft. to 90 ft. From 45 ft. to 90 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 3 ft. to 45 ft. From 45 ft. to 90 ft. From 90 ft. to 90 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? Northwest How many feet? 90

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top Soil			
2	30	clay			
30	90	red / green shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-10-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 5-15-94 under the business name of Weninger Drilling by (signature) Karina Morrisey

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.