	WATE								
1 LOCATION OF WATER WELL: COUNTY: 038 HAMILTON	¦ Fraction ¹ SW 1/4 SW	1/ 4 SE	1/4 ; ;	Section Nu	nber :	Township No		_	
Distance and direction fro APPROX. 14.0 MILES SOUTH A			address of w	ell if lo	cated withi	n city?			
2 WATER WELL DWNER: RR#, St. Address, Box # :		TE		Boar	i of Agricu	lture, Div	ision of	Water Reso	urces
City, State, ZIP code :	SYRACUSE, KS	67878-		App1	ication Num	ber: 6,39	7		
3 LOCATE WELL'S LOCATION WIT AN "X" IN SECTION BOX:		PTH OF COMPLET pth(s) Groundw			EVATION: 1. 218	0 ft. 2	. 0 f	t. 3.	0 ft
/ \	1 1 1	'S STATIC WATE Pump tes	R LEVEL 2 stdata: Wel						
	- • •	mated Yield	O gpm: We	ell water	as Of	t. after	0 hour	s pumping	0 gp
M	; ;; E ; Bore	Hole Diameter		24 in. to	600 ft.,	and	in. to	0 ft.	
l ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ;		WATER TO BE U	JSED AS: 02	IRRIGATIO	٧				;
: SW: S		a chemical/bac	teriologica				-	ll dicinfe	-110 N-
5 TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land s	01 STEEL 16 in. to 6		JOINTS: WEI	.DED 0 ft	., Dia	in. to	0 ft.		
5 TYPE OF BLANK CASING USED:	01 STEEL 16 in. to 6 urface 12 in., ION MATERIAL: 01	CASING 00 ft., Dia weight STEEL	JOINTS: WEI	.DED 0 ft	., Dia	in. to	0 ft.		
5 TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land s TYPE OF SCREEN OR PERFORAT	01 STEEL 16 in. to 6 urface 12 in., ION MATERIAL: 01 INGS ARE: 01	CASING 00 ft., Dia weight STEEL CONT. SLOT	JOINTS: WEI in. to 42 lbs/fr 293 ft., i	DED 0 ft. Wall t	., Dia hickness or ft. to 4	in. to gauge No.	0 ft.		
5 TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land s TYPE OF SCREEN OR PERFORAT SCREEN OR PERFORATION OPEN	01 STEEL 16 in. to 6 urface 12 in., ION MATERIAL: 01 INGS ARE: 01 S: From	CASING 00 ft., Dia weight STEEL CONT. SLOT	JOINTS: WEI in. to 42 lbs/fr 293 ft., i	DED 0 ft. Wall t	., Dia hickness or ft. to 4	in. to gauge No.	0 ft.		
5 TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land s TYPE OF SCREEN OR PERFORATION OPEN SCREEN OR PERFORATED INTERVAL GRAVEL PACK INTERVAL 6 GROUT MATERIAL 03 BENTO Grout Intervals: From What is the nearest source	01 STEEL 16 in. to 6 urface 12 in., ION MATERIAL: 01 INGS ARE: 01 S:	CASING OO ft., Dia weight STEEL CONT. SLOT 253 ft. to 361 ft. to 20 ft. to 0 ft. to	JOINTS: WEI in. to 42 lbs/ff 293 ft., i 411 ft., i 600 ft., i 0 ft., i	DED 0 ft.,	., Dia hickness or ft. to 4 ft. to 6 ft. to	in. to gauge No. 60 ft. 00 ft.	0 ft.		
5 TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land s TYPE OF SCREEN OR PERFORAT SCREEN OR PERFORATION OPEN SCREEN PERFORATED INTERVAL GRAVEL PACK INTERVAL 6 GROUT MATERIAL 03 BENTO Grout Intervals: From What is the nearest source Direction from well? WEST	O1 STEEL 16 in. to 6 urface 12 in., ION MATERIAL: 01 INGS ARE: 01 S: From From From From Oft. to 20 f of possible cont	CASING OO ft., Dia weight STEEL CONT. SLOT 253 ft. to 361 ft. to 20 ft. to 0 ft. to t., From amination: 14	JOINTS: WEI in. to 42 lbs/ff 293 ft., i 411 ft., i 600 ft., i 0 ft., i	DED 0 ft.,	ft. to 4 ft. to 6 ft. to ft. to	in. to gauge No. 60 ft. 00 ft. 0 ft. 1 ft. to	0 ft.	low many fe	
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land s TYPE OF SCREEN OR PERFORAT SCREEN OR PERFORATION OPEN SCREEN PERFORATED INTERVAL GRAVEL PACK INTERVAL GRAVEL PACK INTERVAL 6 GROUT MATERIAL 03 BENTO Grout Intervals: From What is the nearest source Direction from well? WEST FROM ; TO ; 0 ; 2 ; 01 CLA 2 ; 55 ; 01 CLA 55 ; 75 ; 05 SAN	O1 STEEL 16 in. to 6 urface 12 in., ION MATERIAL: 01 INGS ARE: 01 S: From From From From Oft. to 20 f of possible cont LITHOLOG Y Y 31 CALICHE	CASING OO ft., Dia weight STEEL CONT. SLOT 253 ft. to 361 ft. to 20 ft. to 0 ft. to t., From amination: 14	JOINTS: WEI in. to 42 lbs/ff 293 ft., i 411 ft., i 600 ft., i 0 ft., i	DED 0 ft.,	ft. to 4 ft. to 6 ft. to ft. to	in. to gauge No. 60 ft. 00 ft. 0 ft. 1 ft. to	0 ft.		
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land s TYPE OF SCREEN OR PERFORAT SCREEN OR PERFORATION OPEN SCREEN PERFORATED INTERVAL GRAVEL PACK INTERVAL GRAVEL PACK INTERVAL GRAVEL PACK INTERVAL Direction from well? WEST FROM TO :	O1 STEEL 16 in. to 6 urface 12 in., ION MATERIAL: 01 INGS ARE: 01 S: From From From From Oft. to 20 f of possible cont LITHDLOG Y Y 31 CALICHE D Y 20 LIMESTONE 07 Y 07 FINE SAND 08	CASING OO ft., Dia weight STEEL CONT. SLOT 253 ft. to 361 ft. to 20 ft. to 0 ft. to t., From amination: 14 IC LOG	JOINTS: WEI in. to 42 lbs/ff 293 ft., i 411 ft., i 600 ft., i 0 ft., i	DED 0 ft.,	ft. to 4 ft. to 6 ft. to ft. to	in. to gauge No. 60 ft. 00 ft. 0 ft. 1 ft. to	0 ft.	low many fe	
STYPE OF BLANK CASING USED: Blank casing diameter Casing height above land s TYPE OF SCREEN OR PERFORAT SCREEN OR PERFORATION OPEN SCREEN PERFORATED INTERVAL GRAVEL PACK INTERVAL GRAVEL PACK INTERVAL 6 GROUT MATERIAL 03 BENTO Grout Intervals: From What is the nearest source Direction from well? WEST FROM : TO : 0 : 2 : 01 CLA 2 : 55 : 01 CLA 55 : 75 : 05 SAN 75 : 117 : 01 CLA 117 : 123 : 01 CLA 117 : 123 : 01 CLA 123 : 135 : 01 CLA 135 : 138 : 01 CLA	O1 STEEL 16 in. to 6 urface 12 in., ION MATERIAL: 01 INGS ARE: 01 S: From From From From From S: From From V 20 timestone 07 Y 20 timestone	CASING OO ft., Dia weight STEEL CONT. SLOT 253 ft. to 361 ft. to 20 ft. to 0 ft. to t., From amination: 14 IC LOG	JOINTS: WEI in. to 42 lbs/ff 293 ft., i 411 ft., i 600 ft., i 0 ft., i	DED 0 ft.,	ft. to 4 ft. to 6 ft. to ft. to	in. to gauge No. 60 ft. 00 ft. 0 ft. 1 ft. to	0 ft.	low many fe	
5 TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land s TYPE OF SCREEN OR PERFORATION OPEN SCREEN OR PERFORATION OPEN SCREEN PERFORATED INTERVAL GRAVEL PACK INTERVAL 6 GROUT MATERIAL O3 BENTO Grout Intervals: From What is the nearest source Direction from well? WEST FROM	O1 STEEL 16 in. to 6 urface 12 in., ION MATERIAL: 01 INGS ARE: 01 S: From From From From From S: From From V 20 timestone 07 Y 20 timestone	CASING OO ft., Dia weight STEEL CONT. SLOT 253 ft. to 361 ft. to 20 ft. to 0 ft. to t., From amination: 14 IC LOG	JOINTS: WEI in. to 42 lbs/ff 293 ft., i 411 ft., i 600 ft., i 0 ft., i	DED 0 ft.,	ft. to 4 ft. to 6 ft. to ft. to	in. to gauge No. 60 ft. 00 ft. 0 ft. 1 ft. to	0 ft.	low many fe	

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 05/01/92 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 145 This Water Well Record was completed on (mo/day/yr) 06/08/92 under the business name of HENKLE DRILLING & SUPPLY by (signature)

Then the business name of HENKLE DRILLING & SUPPLY by (signature)

11 LOCATION OF WATER WELL: Fraction ! Section Number | Township Number | Range Number COUNTY: 038 HAMILTON | SW 1/4 SW 1/4 SE 1/4 | 22 | T 26 S | R 42 12 WATER WELL OWNER: MRS. DOROTHY WHITE : RR#, St. Address, Box # : P.O. BOX 304 Board of Agriculture, Division of Water Resources City, State, ZIP code : SYRACUSE, KS 67878-Application Number: 6,397 FROM ; TO ; LITHOLOGIC LOG 203 ; 205 ; 28 ROCK 205 | 232 | 19 SHALE 232 ; 293 ; 23 SANDSTONE 19 SHALE 29 ROCK & SAND 293 : 295 : 01 CLAY 295 361 : 19 SHALE 20 LIMESTONE

17 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was : completed on (mo/day/year) 05/01/92 and this record is true to the best of my knowledge and belief. Kansas This Water Well Record was completed on (mo/day/yr) 06/08/92 Water Well Contractor's License No. 145

under the business name of HENKLE DRILLING & SUPPLY

by (signature) Douglas A. Henkle