

1 LOCATION OF WATER WELL: County: <u>Reno.</u>	Fraction <u>SW</u> $\frac{1}{4}$ <u>NW</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$	Section Number <u>5</u>	Township Number T <u>26</u> S	Range Number R <u>5</u> E <u>W</u>
---	--	-------------------------	-------------------------------	------------------------------------

Distance and direction from nearest town or city street address of well if located within city?
5 South 6 1/2 West HADEN Ks.

2 WATER WELL OWNER: Richard. Neal
RR#, St. Address, Box # : PR #
City, State, ZIP Code : Pretty Prairie 67570

Board of Agriculture, Division of Water Resources
Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL. 65 ft. ELEVATION: _____

Depth(s) Groundwater Encountered 1. 14 ft. 2. _____ ft. 3. _____ ft.

WELL'S STATIC WATER LEVEL 14 ft. below land surface measured on mo/day/yr 4-5-91

Pump test data: Well water was 16 ft. after 12 hours pumping 20 gpm

Est. Yield 30 gpm: Well water was _____ ft. after _____ hours pumping _____ gpm

Bore Hole Diameter 11 in. to 65 ft., and _____ in. to _____ ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	9 Dewatering
	<u>7 Lawn and garden only</u>	10 Monitoring well
		12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes _____ No X; If yes, mo/day/yr sample was submitted _____

Water Well Disinfected? Yes X No _____

TYPE OF BLANK CASING USED:		3 Wrought iron		5 Concrete tile		CASING JOINTS: Glued ☒ Clamped ☐	
1 Steel		3 RMP (SR)		6 Asbestos-Cement		9 Other (specify below)	
2 PVC		4 ABS		7 Fiberglass		Welded ☐	
Blank casing diameter		5 in. to 20 ft., Dia		in. to . ft., Dia		Threaded ☐	
Casing height above land surface		12 in., weight 2.59		lbs./ft. Wall thickness or gauge No. 160 PSI			
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel		3 Stainless steel		5 Fiberglass		7 PVC	
2 Brass		4 Galvanized steel		6 Concrete tile		8 RMP (SR)	
						9 ABS	
						10 Asbestos-cement	
						11 Other (specify)	
						12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot		2 Mill slot		5 Gauzed wrapped		8 Saw cut	
2 Louvered shutter		4 Key punched		6 Wire wrapped		11 None (open hole)	
				7 Torch cut		9 Drilled holes	
						10 Other (specify)	
SCREEN-PERFORATED INTERVALS:							
From		20 ft. to 65		ft., From		ft. to . ft.	
GRAVEL PACK INTERVALS:							
From		20 ft. to 65		ft., From		ft. to . ft.	

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 20 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? North How many feet? 50

[illegible]

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-5-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 378 This Water Well Record was completed on (mo/day/yr) 4-24-91 under the business name of Wenger & Dullin by (signature) [Signature]