


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Reno	NE 1/4 NW 1/4 NW 1/4	31	T 26 S	R 5 E/W

Distance and direction from nearest town or city street address of well if located within city?

Approximately 10 miles west of St. Joe

2 WATER WELL OWNER:	Equus Beds GMD No. 2	Board of Agriculture, Division of Water Resources Application Number:
RR#, St. Address, Box #:	313 Spruce	
City, State, ZIP Code:	Halstead, KS 67056-1925	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 33 ft. ELEVATION: unknown
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 9'5" ft. below land surface measured on mo/day/yr 8-7-91
	Pump test data: Well water was not ch'd ft. after hours pumping gpm
	Est. Yield unknown gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 6 in. to 53 ft. and in. to ft.
WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No x; If yes, mo/day/yr sample was submitted	Water Well Disinfected? Yes No x

5 TYPE OF BLANK CASING USED:	5 Wrought iron 8 Concrete tile CASING JOINTS: Glued x Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded	
2 PVC 4 ABS 7 Fiberglass Threaded x	
Blank casing diameter 2 in. to 7 ft. Dia 2 in. to 20 ft. Dia in. to ft.	
Casing height above land surface 36 in. weight 70-PVC 3.65-steel lbs./ft. Wall thickness or gauge No. 154 PVC & steel	
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 20 ft. to 30 ft. From ft. to ft.	
GRAVEL PACK INTERVALS: From 15 ft. to 30 ft. From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement 2 Cement grout 3 Bentonite 4 Other Bentonite Holeplug
Grout Intervals: From ft. to ft. From ft. to ft. From 0 ft. to 15 ft.	
What is the nearest source of possible contamination:	10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None known	

Direction from well?		How many feet?	
FROM	TO	FROM	TO
0	3	LITHOLOGIC LOG	
3	15	Topsoil, sandy	
15	25	Sand and gravel, fine to medium to coarse, loose, clean	
25	30	Sand, fine to very fine, loose, clean	
30	38	Gravel, medium, streaks of clay	
38	40	Clay, tan, sandy	
40	49	Clay, tan, hard	
49	53	Clay, tan	
		Shale, red	
		PLUGGING INTERVALS	

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-7-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 9-5-91 under the business name of Clarke Well & Equipment, Inc. by (signature)
