

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Reno		NW 1/4 NW 1/4 NE 1/4		31		T 26 S		R 5 E/W	
Distance and direction from nearest town or city street address of well if located within city?									
Approximately 2 miles south and 5 1/2 miles east of Pretty Prairie									
2 WATER WELL OWNER:		Equus Beds GMD #2							
RR#, St. Address, Box # :		313 Spruce							
City, State, ZIP Code :		Halstead, KS 67056-1925							
		Board of Agriculture, Division of Water Resources							
		Application Number:							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 53 ft. ELEVATION: unknown							
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL Approx. 6 ft. below land surface measured on mo/day/yr							
		Pump test data: Well water was not ch'd. ft. after hours pumping gpm							
		Est. Yield unknown gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 6 1/2 in. to 55 ft. and in. to ft.							
		WELL WATER TO BE USED AS:							
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes No X							
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped							
1 Steel		3 RMP (SR)							
2 PVC		4 ABS							
Blank casing diameter steel 2 in. to 7 ft. Dia PVC 2 in. to 40 ft. Dia		6 Asbestos-Cement							
Casing height above land surface steel 36 in., weight steel 3.65 PVC .70 lbs./ft. Wall thickness or gauge No. 154		7 Fiberglass							
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement							
1 Steel		3 Stainless steel							
2 Brass		4 Galvanized steel							
5 Fiberglass		8 RMP (SR)							
6 Concrete tile		9 ABS							
11 Other (specify)		12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped							
1 Continuous slot		3 Mill slot							
2 Louvered shutter		4 Key punched							
6 Wire wrapped		7 Torch cut							
10 Other (specify)		8 Saw cut							
11 None (open hole)		9 Drilled holes							
SCREEN-PERFORATED INTERVALS:		From 40 ft. to 50 ft. From ft. to ft.							
GRAVEL PACK INTERVALS:		From 35 ft. to 55 ft. From ft. to ft.							
6 GROUT MATERIAL:		1 Neat cement							
Grout Intervals: From ft. to ft. From ft. to ft. From 0 ft. to 35 ft.		2 Cement grout							
What is the nearest source of possible contamination:		3 Bentonite							
1 Septic tank		4 Lateral lines							
2 Sewer lines		5 Cess pool							
3 Watertight sewer lines		6 Seepage pit							
7 Pit privy		8 Sewage lagoon							
9 Feedyard		10 Livestock pens							
11 Fuel storage		12 Fertilizer storage							
13 Insecticide storage		14 Abandoned water well							
15 Oil well/Gas well		16 Other (specify below)							
None known		How many feet?							
Direction from well?									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 4 Topsoil, sandy									
4 6 Clay, red, soft, silty									
6 24 Sand and gravel, fine, medium, loose, clean									
24 49 Clay, tan, hard, silty									
49 55 Shale, red, hard									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-11-92 and this record is true to the best of my knowledge and belief Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 3-2-92 under the business name of Clarke Well & Equipment, Inc. by (signature) Darrell W. Clarke									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									