

A4

2311068

WATER WELL RECORD

Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:

County: Ind

Distance and direction from nearest town or city street address of well if located within city? 3'E, 34'S & SW corner 124 E Main

Fraction: NW 1/4 SW 1/4 SE 1/4

Section Number: 18

Township Number: T 26 S

Range Number: R 6 E

2 WATER WELL OWNER:

RR#, St. Address, Box #: KDE Forbes Field, Bldg 740

City, State, ZIP Code: Topeka KS 66620-0001

Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1 Mile

W E

NW	NE
SW	SE

S

4 DEPTH OF COMPLETED WELL: 45 ft. **ELEVATION:** 26 ft.

Depth(s) Groundwater Encountered 1. 26 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL NA ft. below land surface measured on mo/day/yr NA

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 8 in. to ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile
2 <u>PVC</u>	4 ABS	6 Asbestos-Cement	9 Other (specify below)
		7 Fiberglass	

Blank casing diameter 2 in. to ft., Dia. in. to ft., Dia. in. to ft.

Casing height above land surface Flush in., weight 203 lbs./ft. Wall thickness or gauge No. Sch 40

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	2 <u>Mill slot</u>	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
		7 Torch cut	10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 43 ft. to 45 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 42.5 ft. to 45 ft., From ft. to ft.

6 GROUT MATERIAL:

Grout Intervals: From 3 ft. to 42.5 ft., From 3 ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
			13 Insecticide storage

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG
0.0	0.5	Concrete
0.5	3.0	Clay
3.0	45.0	Sand

FROM	TO	PLUGGING INTERVALS

Allison Irwin wrote to Don Taylor requesting additional waivers for this site on 2-15-96.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-3-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 5-15-96 under the business name of GSI by (signature) Allison Irwin

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4