

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: PEND		NW 1/4 NW 1/4 NW 1/4		8 18		T 26 44 S		R 18W 6 EW	
Distance and direction from nearest town or city street address of well if located within city?									
124 E. MAIN STREET PRETTY PRAIRIE, KS WELL ID--AS 01									
2 WATER WELL OWNER:		ROBERT KRIEBEL							
RR#, St. Address, Box # :		124 E. MAIN STREET							
City, State, ZIP Code :		PRETTY PRAIRIE, KS Board of Agriculture, Division of Water Resources							
		Application Number:							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 40 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL . 23.65 . . . ft. below land surface measured on mo/day/yr . 5/7/95 . Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter . 7.75 . . . in. to 40 . . . ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was sub- mitted Water Well Disinfected? Yes No X							
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped							
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile Welded							
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below) Threaded							
Blank casing diameter . 2 in. to 30 ft. Dia in. to ft. Dia in. to ft.									
Casing height above land surface -6 in., weight lbs./ft. Wall thickness or gauge No.									
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) . . . Sch 40									
SCREEN-PERFORATED INTERVALS: From 30 ft. to 40 ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 27.5 ft. to 40 ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout intervals: From 22.5 ft. to 27.5 ft. From 0 ft. to 22.5 ft. From ft. to ft.									
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well							
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage									
Direction from well?		How many feet?							
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS				
0.0	0.5	CONCRETE							
0.5	7.0	SANDY CLAY							
7.0	40.0	SAND							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/16/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 549 This Water Well Record was completed on (mo/day/yr) 6/21/95 under the business name of J S R DRILLING SERVICES, INC. by (signature) Ray Coors									