WATE	R WE	LL RECORD	Form WV	WC-5	Division of Wate	r Resources App. N	48,294	
1 LOCATION OF WATER WELL:		Fraction		Section Number	Township No.	Range Number		
County: Reno SE 1/4 SW 1/4			SE 1/4 SW 1/4 NE	1/4 NW 1/4	6	T 26 S	R6 □E 🗹 W	
		Address of Well Location;		Global Positioning System (GPS) information:				
fron	from nearest town or intersection: If at owner's address, check here .					Latitude: .37.817561 (in decimal degrees)		
2 m	2 miles North of Pretty Prairie, Kansas					Longitude: 98.021898 (in decimal degrees) Elevation: 1578 Ft		
						-t	••••	
2 WATER WELL OWNER: David Krehhiel						<u>Datum</u> : ☐ WGS 84, ☑ NAD 83, ☐ NAD 27		
David Allinois					Collection Method:	0.7.1.1		
C'A CAA ZID CA					☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
City, State, ZIP Code : Pratt. Kansas 67124					Est. Accuracy: \square <3 m, \square 3-5 m, \square 5-15 m, \square >15 m			
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 63								
	'H AN "X	"IN 4 DEPTH OF C	COMPLETED WELL	, 63	ft.	AT WILL		
SEC	SECTION BOX: Depth(s) Groundwater Encountered (1)							
	WELL'S STATIC WATER LEVEL32ft. below land surface measured on mo/day/yr1/13/20							
	Pump test data: Well water wasft. after hours pumping							
	EST. YIELD. 250-36pm. Well water was							
W								
		WELL WAIER	TO BE USED AS:	Public water	er supply	othermal Us	njection well	
S'	SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)							
	S					Yes V INo		
	S If yes, mo/day/yr sample was submitted							
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter								
Casing height above land surface								
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify)								
☐ Steel ☐ Stainless Steel ☑ PVC ☐ Other (Specify)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS: From 43 ft. to 63 ft., From ft. to ft.								
From								
GRAVEL PACK INTERVALS: From 20 ft. to 63 ft., From ft. to ft.								
From								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From0								
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well								
	Watertig	ht sewer lines	t Feedvard	Fertilizer sto				
Direc		m well . None within 1/4 n	nile	Distance f				
FROM	ТО	LITHOLOGI	IC LOG	FROM	TO LITHO. LC	G (cont.) or PLU	GGING INTERVALS	
0	1	Topsoil					711111	
1	17	Clay, brown					What .	
17	43	Sand, fine w/clay streak	S					
43	63	Sand, medium						
63	65	Shale, gray					2740	
		·····						
		70						
		1984						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year)!/13/2016 and this record is true to the best of my knowledge and belief								
Kansas Water Well Contractor's License No								
under the	e busines	ss name of Peterson McI	Nett Utilling, Inc.		by (signature) 763	41414Vest		
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send one copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								