

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Reo</u>	<u>SE 1/4 SE 1/4 SE 1/4</u>	<u>18</u>	T <u>26</u> S	R <u>6</u> EW

Distance and direction from nearest town or city street address of well if located within city?

S.E. Corner of Pretty Prairie

2 WATER WELL OWNER:	RR#, St. Address, Box # :	City, State, ZIP Code :	Board of Agriculture, Division of Water Resources
<u>Randy Schrag</u>	<u>Box 86</u>	<u>Pretty Prairie, KS 67570</u>	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>78</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>34</u> ft. below land surface measured on mo/day/yr <u>12-3-88</u> Pump test data: Well water was <u>37</u> ft. after <u>1</u> hours pumping <u>25</u> gpm Est. Yield gpm Well water was ft. after hours pumping gpm Bore Hole Diameter <u>8</u> in. to <u>8.2</u> ft., and in. to ft. WELL WATER TO BE USED AS: ☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No <u>X</u>; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
<u>2 PVC</u>	4 ABS	7 Fiberglass	Welded
Blank casing diameter <u>5</u> in. to <u>6.8</u> ft., Dia. in. to ft., Dia. in. to ft.			Threaded
Casing height above land surface <u>12</u> in., weight lbs./ft. Wall thickness or gauge No. <u>160</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:	<u>2 PVC</u>	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	<u>8</u> Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From <u>6.8</u> ft. to <u>7.8</u> ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From <u>6.5</u> ft. to <u>8.2</u> ft., From ft. to ft.			

6 GROUT MATERIAL:	<u>1</u> Neat cement	2 Cement grout	<u>3</u> Bentonite	4 Other
Grout Intervals: From <u>3</u> ft. to <u>23</u> ft., From <u>6.0</u> ft. to <u>6.5</u> ft., From ft. to ft.				
What is the nearest source of possible contamination:	<u>1</u> Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well? <u>SW</u>				How many feet? <u>105</u>

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>8</u>	<u>Sandy silt</u>			
<u>8</u>	<u>10</u>	<u>Gr clay</u>			
<u>10</u>	<u>50</u>	<u>Sand + sm Gravel</u>			
<u>50</u>	<u>60</u>	<u>F Sand</u>			
<u>60</u>	<u>68</u>	<u>Br Clay</u>			
<u>68</u>	<u>82</u>	<u>Sand + sm Gravel</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>12-9-88</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>447</u> This Water Well Record was completed on (mo/day/yr) <u>12-27-88</u> under the business name of <u>Miller Drilling</u> by (signature) <u>Eva Miller</u>
