

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number																																																													
County: Reno Montezuma		SE 1/4 NW 1/4 SW 1/4		18		T 26S S		R 6W 7W																																																													
Distance and direction from nearest town or city street address of well if located within city?																																																																					
2 WATER WELL OWNER: Gene Bowyer																																																																					
RR#, St. Address, Box #: Pretty Prairie, Kansas 67570					Board of Agriculture, Division of Water Resources																																																																
City, State, ZIP Code: 327 N Rhodes (CITY)					Application Number:																																																																
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 80' ft. ELEVATION:																																																																		
			Depth(s) Groundwater Encountered 1. 32' ft. 2. 31' ft. 3. 31' ft.																																																																		
			WELL'S STATIC WATER LEVEL: 31' ft. below land surface measured on mo/day/yr April 30-91																																																																		
			Pump test data: Well water was NA ft. after NA hours pumping NA gpm																																																																		
			Est. Yield NA gpm: Well water was NA ft. after NA hours pumping NA gpm																																																																		
			Bore Hole Diameter: 7 7/8" in. to 80' ft. and NA in. to NA ft.																																																																		
			WELL WATER TO BE USED AS:																																																																		
			☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below) ☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well																																																																		
Was a chemical/bacteriological sample submitted to Department? Yes XX No XX ; If yes, mo/day/yr sample was submitted																																																																					
Water Well Disinfected? Yes X No																																																																					
5 TYPE OF BLANK CASING USED:																																																																					
☒ 1 Steel ☐ 3 RMP (SR) ☐ 5 Wrought iron ☐ 8 Concrete tile CASING JOINTS: Glued XX Clamped ☒ 2 PVC ☐ 4 ABS ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) Welded ☐ 7 Fiberglass Threaded																																																																					
Blank casing diameter 5" in. to 72' ft. Dia 14" in. to 160 lbs./ft. Wall thickness or gauge No. SDR26																																																																					
Casing height above land surface 14" in. weight 160 lbs./ft. Wall thickness or gauge No. SDR26																																																																					
TYPE OF SCREEN OR PERFORATION MATERIAL:																																																																					
☒ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☐ 8 RMP (SR) ☐ 10 Asbestos-cement ☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 11 Other (specify) ☐ 12 None used (open hole)																																																																					
SCREEN OR PERFORATION OPENINGS ARE:																																																																					
☐ 1 Continuous slot ☐ 3 Mill slot ☐ 5 Gauzed wrapped ☒ 8 Saw cut ☐ 11 None (open hole) ☐ 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes ☐ 7 Torch cut ☐ 10 Other (specify)																																																																					
SCREEN-PERFORATED INTERVALS: From 72' ft. to 80' ft. From 80' ft. to 24' ft. From 24' ft. to 80' ft.																																																																					
GRAVEL PACK INTERVALS: From 80' ft. to 24' ft. From 24' ft. to 80' ft.																																																																					
6 GROUT MATERIAL: ☐ 1 Neat cement ☒ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other																																																																					
Grout Intervals: From 24' ft. to 2' ft. From 2' ft. to 250' ft.																																																																					
What is the nearest source of possible contamination:																																																																					
☐ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☒ 10 Livestock pens ☐ 14 Abandoned water well ☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well ☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below) ☐ 13 Insecticide storage																																																																					
Direction from well? West How many feet? 250'																																																																					
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th style="width:10%;">FROM</th> <th style="width:10%;">TO</th> <th style="width:40%;">LITHOLOGIC LOG</th> <th style="width:10%;">FROM</th> <th style="width:10%;">TO</th> <th style="width:20%;">PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>0'</td> <td>4'</td> <td>Top soil</td> <td></td> <td></td> <td></td> </tr> <tr> <td>4'</td> <td>9'</td> <td>Clay.</td> <td></td> <td></td> <td></td> </tr> <tr> <td>9'</td> <td>17'</td> <td>Sandy clay.</td> <td></td> <td></td> <td></td> </tr> <tr> <td>17'</td> <td>29'</td> <td>Fine sand.</td> <td></td> <td></td> <td></td> </tr> <tr> <td>29'</td> <td>33'</td> <td>Clay.</td> <td></td> <td></td> <td></td> </tr> <tr> <td>33'</td> <td>48'</td> <td>Medium Fine sand.</td> <td></td> <td></td> <td></td> </tr> <tr> <td>48'</td> <td>65'</td> <td>Clay.</td> <td></td> <td></td> <td></td> </tr> <tr> <td>65'</td> <td>80'</td> <td>Course Sand & Fine Gravel.</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>Red Bed.</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>										FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0'	4'	Top soil				4'	9'	Clay.				9'	17'	Sandy clay.				17'	29'	Fine sand.				29'	33'	Clay.				33'	48'	Medium Fine sand.				48'	65'	Clay.				65'	80'	Course Sand & Fine Gravel.						Red Bed.			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																																
0'	4'	Top soil																																																																			
4'	9'	Clay.																																																																			
9'	17'	Sandy clay.																																																																			
17'	29'	Fine sand.																																																																			
29'	33'	Clay.																																																																			
33'	48'	Medium Fine sand.																																																																			
48'	65'	Clay.																																																																			
65'	80'	Course Sand & Fine Gravel.																																																																			
		Red Bed.																																																																			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) April 30 - 91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 112 This Water Well Record was completed on (mo/day/yr) May 28 - 91 under the business name of Wells Drilling Co. by (signature) <i>Wells</i>																																																																					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																																																																					