


MW-2 2211074

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: RENO		Fraction: SW 1/4 NW 1/4 SE 1/4	Section Number: 18	Township Number: T 26 S	Range Number: R 6 E
Distance and direction from nearest town or city street address of well if located within city? NE CORNER OF ELM + MAIN PRETTY PRAIRIE, KS					
2 WATER WELL OWNER: KOHE FORBES FIELD BLDG. 140 RR#, St. Address, Box # : City, State, ZIP Code : TOPEKA, KS 66620		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 34 ft. ELEVATION: Depth(s) Groundwater Encountered: 25.29 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: 25.29 ft. below land surface measured on mo/day/yr 12-28-94 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm Well water was ft. after hours pumping gpm Bore Hole Diameter: 8 in. to ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Blank casing diameter: 2 in. to ft. Dia. in. to ft. Dia. in. to ft. Dia. in. to ft. Dia. Casing height above land surface: FLUSH in. weight: 1703 lbs./ft. Wall thickness or gauge No. 154		CASING JOINTS: Glued Clamped Welded Threaded FLUSH			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)		SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 19 ft. to 34 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 19 ft. to 34 ft. From ft. to ft. From ft. to ft. From ft. to ft.		6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 19 ft. to 2 ft. From ft. to ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below) Direction from well? SW How many feet? 170			
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0.0	3.0	TOPSOIL, SILT, SAND			
3.0	8.0	CLAY, SILT, SAND			
8.0	14.0	SAND, SILT			
14.0	34.0	SAND			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-28-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 1-3-95 under the business name of GSI by (signature) Mike Simpson					

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.