


1 LOCATION OF WATER WELL: County: Reno		Fraction: Center $\frac{1}{4}$ NE $\frac{1}{4}$	Section Number: 14	Township Number: T 26 S	Range Number: R 7 E/W
Distance and direction from nearest town or city street address of well if located within city? 1 Mile West 3/4 Mile North 1/4 Mile West Of Pretty Prairie, Kans.					
2 WATER WELL OWNER: Lawrence R. Kaufman RR#, St. Address, Box #: 1621 Ridge RD. City, State, ZIP Code: Derby, Kansas 67037		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 102 ft. ELEVATION: Depth(s) Groundwater Encountered: 1. 46' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: 46' ft. below land surface measured on mo/day/yr June 5 - 1995 Pump test data: Well water was ft. after hours pumping gpm Est. Yield: NA gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: 28" in. to 102' ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) XX Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No XX ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) XXX2 PVC 4 ABS Blank casing diameter: 0.49 in. to 60' ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface: App. 12" in., weight 16,150 Per. FT. lbs./ft. Wall thickness or gauge No. 0.49		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued XX Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 102' ft. to 42' ft. From ft. to ft. GRAVEL PACK INTERVALS: From ft. to ft. From ft. to ft. From 102' ft. to 26' ft. From ft. to ft.			
6 GROUT MATERIAL: XX Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 26' ft. to 0' ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens X 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? South West How many feet? App. 40'		LITHOLOGIC LOG FROM TO 1' 9' Top Soil/ Sandy Clay. 9' 23' Sandy Clay. 23' 30' Clay. 30' 40' Course Sand (Dark). 40' 41' Clay. 41' 80' Course Sand & Fine Gravel. 80' 95' Clay. 95' 102' Course Sand & Fine Gravel. Red Bed.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) May 15 - 1995 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 112 This Water Well Record was completed on (mo/day/yr) June 8 - 1995 under the business name of WELLS DRILLING CO. by (signature) <i>Dal Wells</i>		PLUGGING INTERVALS FROM TO			