


1 LOCATION OF WATER WELL:		Fraction	Section Number		Township Number	Range Number
County: <u>Reno</u>		NW 1/4 NW 1/4 NW 1/4	<u>3</u>		T <u>26</u> S	R <u>7</u> E/W
Distance and direction from nearest town or city street address of well if located within city? <u>Approximately 3 Miles North and 3 Miles West of Pretty Prairie</u>						
2 WATER WELL OWNER: <u>Equus Beds GMD #2</u>						
RR#, St. Address, Box # : <u>313 Spruce</u>				Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : <u>Halstead, KS 67056-1925</u>				Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>52</u> ft. ELEVATION: <u>Unknown</u>				
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.				
		WELL'S STATIC WATER LEVEL <u>36.7</u> ft. below land surface measured on mo/day/yr <u>2-6-92</u>				
		Pump test data: Well water was <u>not ch'd</u> ft. after hours pumping gpm				
		Est. Yield <u>unknown</u> gpm: Well water was ft. after hours pumping gpm				
		Bore Hole Diameter <u>6 1/2</u> in. to <u>50</u> ft., and in. to ft.				
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well						
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)						
2 Irrigation 4 Industrial 7 Lawn and garden only 10 <u>Monitoring well</u>						
Was a chemical/bacteriological sample submitted to Department? Yes.....No... <u>X</u>; If yes, mo/day/yr sample was submitted						
Water Well Disinfected? Yes No <u>X</u>						
5 TYPE OF BLANK CASING USED:						
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped						
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded						
7 Fiberglass Threaded						
Blank casing diameter <u>Steel 2</u> in. to ft., Dia <u>PVC 2</u> in. to <u>39</u> in. to ft.						
Casing height above land surface <u>Steel 36</u> in., weight <u>Steel 3.65/PVC .70</u> lbs./ft. Wall thickness or gauge No. <u>154</u>						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)						
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)						
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes						
7 Torch cut 10 Other (specify)						
SCREEN-PERFORATED INTERVALS: From <u>39</u> ft. to <u>49</u> ft., From ft. to ft.						
From ft. to ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From <u>34</u> ft. to <u>50</u> ft., From ft. to ft.						
From ft. to ft., From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other <u>Bentonite Holeplug</u>						
Grout Intervals: From ft. to ft., From ft. to ft., From <u>0</u> ft. to <u>34</u> ft.						
What is the nearest source of possible contamination:						
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well						
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well						
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)						
13 Insecticide storage None Known						
Direction from well? How many feet?						
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0	4	Topsoil, sandy				
4	6	Clay, brown				
6	14	Sand and gravel, fine, medium, loose, clean				
14	16	Clay, tan, hard, silty				
16	40	Sand and gravel, fine, medium, loose, clean, thin clay streaks				
40	50	Sand, fine, medium, loose, silty				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) <u>reconstructed</u> , or (3) <u>plugged</u> under my jurisdiction and was completed on (mo/day/year) <u>2-6-92</u> and this record is true to the best of my knowledge and belief. Kansas						
Water Well Contractor's License No. <u>185</u> This Water Well Record was completed on (mo/day/yr) <u>2-25-92</u>						
under the business name of <u>Clarke Well & Equipment, Inc.</u> by (signature) <u>Donnell W. Clarke</u>						