

1 LOCATION OF WATER WELL:		Fraction		Section Number	Township Number	Range Number
County: xxxxxx Reno		NE 1/4 NE 1/4 NW 1/4		36	T 26 S	R 8 EW

Distance and direction from nearest town or city street address of well if located within city?

1 1/2 W 6 N Kingman

2 WATER WELL OWNER: Ed Lubbers		Board of Agriculture, Division of Water Resources Application Number:
RR#, St. Address, Box # : Rt 1		
City, State, ZIP Code : Kingman, KS. 67068		

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION:	
		Depth(s) Groundwater Encountered 1. 18 ft. 2. 18 ft. 3. 18 ft.	
		WELL'S STATIC WATER LEVEL 12 ft. below land surface measured on mo/day/yr 2-19-88	
		Pump test data: Well water was 8 gpm: Well water was 30 ft. after 2-19-88 hours pumping 8 gpm	
		Bore Hole Diameter 9 in. to 30 ft. and 30 in. to 30 ft.	
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well	
Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes No	

5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped	
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded	
2 PVC 4 ABS		7 Fiberglass Threaded	
Blank casing diameter 4 in. to 13 ft. Dia 4 from 17 to 30 ft. Dia 4 in. to 30 ft.		Casing height above land surface 18 in. weight 214 lbs./ft. Wall thickness or gauge No. 214	
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement	
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)	
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 13 ft. to 17 ft. From 17 ft. to 30 ft.		GRAVEL PACK INTERVALS: From 13 ft. to 30 ft. From 30 ft. to 30 ft.	

6 GROUT MATERIAL:		1 Neat cement 13 2 Cement grout 3 Bentonite 4 Other	
Grout Intervals: From 0 ft. to 13 ft. From 13 ft. to 30 ft.		What is the nearest source of possible contamination:	
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well		2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)		13 Insecticide storage	
Direction from well? E		How many feet? 60	

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	4	top soil			
4	13	clay			
13	17	sand			
17	30	red shale			
		Could not grout to 20 ft on account of formation.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-19-88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 140 This Water Well Record was completed on (mo/day/yr) 3-4-88 under the business name of Lyman Inc. by (signature) <i>Ed Lubbers</i>	
---	--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks. underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T 26 R 8

EW SEC. 36

1/4

1/4

1/4