

1 LOCATION OF WATER WELL: County: <u>Sedgwick</u>	Fraction <u>NE 1/4 NE 1/4 NE 1/4</u>	Section Number <u>21</u>	Township Number <u>T 27 S</u>	Range Number <u>R 1 E</u>
--	---	-----------------------------	----------------------------------	------------------------------

Distance and direction from nearest town or city street address of well if located within city?

7210 W. Central, Wichita, KS.2 WATER WELL OWNER: Amoco Oil Co.RR#, St. Address, Box # : 8700 Indian Creek Pkwy Suite 190

Board of Agriculture, Division of Water Resources

City, State, ZIP Code : Overland Park, KS. 66210

Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 20'9" ft. ELEVATION:Depth(s) Groundwater Encountered 1. 15'10" ft. 2. ft. 3. ft.WELL'S STATIC WATER LEVEL 15.70 ft. below land surface measured on mo/day/yr 6-22-95

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 8'6" in. to 20'9" ft., and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submittedWater Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:

5 Wrought iron

8 Concrete tile

CASING JOINTS: Glued Clamped

1 Steel

3 RMP (SR)

6 Asbestos-Cement

9 Other (specify below)

Welded

2 PVC

4 ABS

7 Fiberglass

Threaded XBlank casing diameter 2.375 in. to 10'3" ft., Dia in. to ft., Dia in. to SDR 13 ft.Casing height above land surface Flush ME in., weight lbs./ft. Wall thickness or gauge No. Sch. 40

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel

3 Stainless steel

5 Fiberglass

7 PVC

10 Asbestos-cement

2 Brass

4 Galvanized steel

6 Concrete tile

8 RMP (SR)

11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

3 Mill slot

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

2 Louvered shutter

4 Key punched

6 Wire wrapped

9 Drilled holes

7 Torch cut

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 20'3" ft. to 10'3" ft., From ft. to ft.

From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 20'9" ft. to 8'6" ft., From ft. to ft.

From ft. to ft., From ft. to ft.

6 GROUT MATERIAL:

1 Neat cement

2 Cement grout3 Bentonite

4 Other

Grout Intervals: From 8'6" ft. to 4' ft., From 4' ft. to 0' ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

14 Abandoned water well

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage FOUR

15 Oil well/Gas well

3 Watertight sewer lines

6 Seepage pit

9 Feedyard

12 Fertilizer storage

16 Other (specify below)

13 Insecticide storage

Direction from well? WestHow many feet? 30'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.50	Gravel-broken concrete			
.50	3	Red brn clay, moist, no odor, mottled, organics.			
3	6	Blk silty clay to clayey silt, faint sulfur odor, moist.			
6	10	Gray-brn gray clayey silt, moist, faint odor, soft.			
10	14.50	Brn sandy clay to clayey sand w/ gray sand mottling, mod.odor, moist to wet at 15'.			
14.50	18	Gray -blk silty sand, mod-strong odor. Poorly sorted, subrounded grains.			
18	19	Blk sandy silt, firm, wet, odor.			
19	20'9"	Tan fine-coarse grained sand, wet, poorly sorted.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-22-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 6-27-95 under the business name of JB Environmental Drilling by signature James Becker