


101450

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction SW 1/4 NE 1/4 NE 1/4	Section Number 34	Township Number T 27 S	Range Number R 1 EW																																																						
Distance and direction from nearest town or city street address of well if located within city? 350' South and 530' West of the Intersection of Harry and Eisenhower Eisenhower																																																											
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Paragon NDT & Finishes BROCARA 1015 West Street Wichita, Kansas 67213		01958009 MW-2 Board of Agriculture, Division of Water Resources Application Number:																																																							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 87 ft. ELEVATION: 1301. Est. Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 11.6 ft. below land surface measured on mo/day/yr 07/18/95 Pump test data: Well water was ft. after hours pumping gpm Est. Yield N/A gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8.25 in. to 87 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X																																																									
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 77 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface 36 in., weight lbs./ft. Wall thickness or gauge No. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 77 ft. to 87 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 75 ft. to 87 ft., From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout intervals: From 0 ft. to 73 ft., From 73 ft. to 75 ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? How many feet? <table border="1"><thead><tr><th>FROM</th><th>TO</th><th>LITHOLOGIC LOG</th><th>FROM</th><th>TO</th><th>PLUGGING INTERVALS</th></tr></thead><tbody><tr><td>0</td><td>7</td><td>Gray-Brown Fat Clay</td><td></td><td></td><td></td></tr><tr><td>7</td><td>18</td><td>Brown, Sandy Fat Clay</td><td></td><td></td><td></td></tr><tr><td>18</td><td>34</td><td>Brown Fine Sand</td><td></td><td></td><td></td></tr><tr><td>34</td><td>40</td><td>Brown, Fine to Medium Sand</td><td></td><td></td><td></td></tr><tr><td>40</td><td>86</td><td>Brown, Fine to Coarse Sand</td><td></td><td></td><td></td></tr><tr><td>86</td><td>87</td><td>Olive-Gray Shale</td><td></td><td></td><td></td></tr><tr><td></td><td>64</td><td>Gray Fat Clay</td><td></td><td></td><td></td></tr><tr><td></td><td>80</td><td>Brown, Fine to Coarse Sand</td><td></td><td></td><td></td></tr></tbody></table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	7	Gray-Brown Fat Clay				7	18	Brown, Sandy Fat Clay				18	34	Brown Fine Sand				34	40	Brown, Fine to Medium Sand				40	86	Brown, Fine to Coarse Sand				86	87	Olive-Gray Shale					64	Gray Fat Clay					80	Brown, Fine to Coarse Sand			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																						
0	7	Gray-Brown Fat Clay																																																									
7	18	Brown, Sandy Fat Clay																																																									
18	34	Brown Fine Sand																																																									
34	40	Brown, Fine to Medium Sand																																																									
40	86	Brown, Fine to Coarse Sand																																																									
86	87	Olive-Gray Shale																																																									
	64	Gray Fat Clay																																																									
	80	Brown, Fine to Coarse Sand																																																									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 08/11/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 9/6/95 under the business name of Terracon Consultants, Inc. by (signature) [Signature]																																																											

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC

1/4

1/4

1/4

CORRECTED
COPY