


1 LOCATION OF WATER WELL: Sedgwick	FRACTION SE 1/4 SE 1/4 SW 1/4	Section Number 3	Township Number T 27 S	Range Number R 1W E/W
--	---	----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

3/8 m. E. of Intersection of 21st N. & Ridge Rd. (N. side) Wichita, KS.

2 WATER WELL OWNER: CITY OF WICHITA	Board of Agriculture, Division of Water Resource
RR#, ST. ADDRESS, BOX #: P.O. Box 9163	
CITY, STATE, ZIP CODE: Wichita, Kansas 67277	Application Number: 950276

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL 40 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 10 FT. BELOW LAND SURFACE MEASURED ON 09/25/1995 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 40 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No
--	---

5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing Diameter 8 in. to 20 ft., Dia in. to ft. Casing height above land surface 24 in., weight 5.52 lbs./ft. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 2 Brass 4 Galvanized steel 6 Concrete tile 7 PVC (SR) SCREEN OR PERFORATION OPENING ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped SCREEN-PERFORATION INTERVALS: from 20 ft. to 30 ft., From ft. to ft. GRAVEL PACK INTERVALS: from 20 ft. to 40 ft., From ft. to ft. FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS	8 Concrete tile CASING JOINTS: Glued X Clamped 9 Other (Specify below) Welded SDR-26 Threaded Wall thickness or gauge No. .332 10 Asbestos-cement 11 other (specify) 12 None used (open hole) 8 Saw cut 11 None (open hole) 9 Drilled holes 10 Other (specify)
--	---

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandon water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage None Apparent Direction from well? How many feet?

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS
0 2 topsoil
2 10 sandy clay
10 40 medium to coarse sand

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 09/25/1995 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 10/05/95 Under the business name of Harp Well & Pump Service, Inc by (signature)
--

Jane Frederick