

OBI

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Seawick</u>		<u>NW 1/4 NW 1/4 NW 1/4</u>	<u>T27</u>	<u>T 29 S</u>	<u>R 1 EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>SE corner of Ridge and Maple, Wichita, KS.</u>					
2 WATER WELL OWNER: <u>Lees Cleaners</u>					
RR#, St. Address, Box #: <u>7125 West Maple</u>				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code: <u>Wichita KS 67209</u>				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>25.50</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>DRY</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>7/4</u> in. to ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well <u>SVE</u> Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>No</u>			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
2 <u>PVC</u>		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
Blank casing diameter <u>2</u> in. to <u>20.50</u> ft. Dia		7 Fiberglass	Threaded		
Casing height above land surface <u>Flush</u> in., weight lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 <u>Mill slot</u>	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
SCREEN-PERFORATED INTERVALS: From <u>20.50</u> ft. to <u>25.50</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>18.50</u> ft. to <u>25.50</u> ft., From ft. to ft.					
6 GROUT MATERIAL:					
1 <u>Neat cement</u>		2 Cement grout	3 Bentonite	4 Other	
Grout intervals: From <u>18.50</u> ft. to <u>25.50</u> ft., From ft. to ft.					
What is the nearest source of possible contamination?					
1 Septic tank		4 Lateral lines	7 Pit privy	10 <u>Livestock pens</u>	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 <u>Fuel storage</u>	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4"	Asphalt Surface	17	19	Brown, moist, firm
4"	1.5 FT	DK. brn, firm silty clay			silty sandy clay.
1.5	2.0	brn. coarse gr. silty sand	19	20	Brown, fine to coarse
2.0	5.0	DK brn, firm, dry silty clay	20	26	gr, moist silty sand
5.0	9.0	DK brn, firm, dry silty clay, sand increasing with depth			Brown to grey moist
9.0	10.0	Brn to Red brn, dry silty clay sand, fine to coarse gr			fine to very coarse gr
10	15	Red brn, moist silty clay sand.			
15	17	Red brn, moist, fine to coarse gr, silty sand.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>9-6-95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>524</u> This Water Well Record was completed on (mo/day/yr) <u>10-13-95</u> under the business name of <u>Allied Labs</u> by (signature) <u>Robert B Brownell</u>					