

1 LOCATION OF WATER WELL: Sedgwick	FRACTION SW 1/4 NE 1/4 SE 1/4	Section Number 20	Township Number T 27 S	Range Number R 1W E/W	
Distance and direction from nearest town or city street address of well if located within city? 118 Arcadia Wichita, Kansas					
2 WATER WELL OWNER: ROBERTS, Don RR & ST. ADDRESS, BOX #: 118 Arcadia CITY, STATE, ZIP CODE: Wichita, Kansas					
Board of Agriculture, Division of Water Resource Application Number:					
3 LOCATE WELL'S LOCATION WITH ANALYTIC SECTION BOX: 	4 DEPTH OF COMPLETED WELL 97 ft. ELEVATION:				
	Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.				
	WELL'S STATIC WATER LEVEL 25 FT. BELOW LAND SURFACE MEASURED ON 10/25/1995				
	Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm : Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 97 ft. and in. to ft.				
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes ☐ No ☒ ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes ☒ No					
5 TYPE OF CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (Specify below) Welded					
7 Fiberglass SDR-26 Threaded					
Blank casing Diameter 5 in. to 77 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 12 in., weight 2.35 lbs. / ft. Wall thickness or gauge No. .214					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENING ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
7 Torch cut 10 Other (specify)					
SCREEN PERFORATION INTERVALS: from 77 ft. to 97 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: from 24 ft. to 97 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout intervals: From 4 ft. to 24 ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandon water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage None Apparent					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	topsoil			
4	18	clay			
18	30	fine sand			
30	35	clay			
35	50	coarse sand			
50	55	clay			
55	65	fine sand			
65	97	medium sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/25/1995 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 11/14/95 Under the business name of Harp Well & Pump Service, Inc by (signature) <i>Jane Frederick</i>					