

1 LOCATION OF WATER WELL: Sedgwick		FRACTION NW 1/4 NE 1/4 SE 1/4		Section Number 19		Township Number T 27 S		Range Number R 1W EW		
Distance and direction from nearest town or city street address of well if located within city? 10726 Meribeuau Ct. Wichita, Kansas										
2 WATER WELL OWNER: SUDERSON, Gopal STREET ADDRESS, BOX #: 10726 Meribeuau Ct. CITY, STATE, ZIP CODE: Wichita, Kansas					Board of Agriculture, Division of Water Resource Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 			4 DEPTH OF COMPLETED WELL 55 ft. ELEVATION:							
			Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 25 FT. BELOW LAND SURFACE MEASURED ON 11/07/1995 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm : Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 55 ft. and in. to ft.							
			WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
			Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No							
5 TYPE OF CASING USED:										
1 Steel			3 RMP (SR)		5 Wrought iron		8 Concrete tile		CASING JOINTS: Glued X Clamped	
2 PVC			4 ABS		6 Asbestos-Cement		9 Other (Specify below)		Welded	
					7 Fiberglass		SDR-26		Threaded	
Blank casing Diameter 5 in. to 35 ft., Dia			in. to 35 ft., Dia		in. to 35 ft., Dia		in. to 35 ft., Dia		in. to 35 ft., Dia	
Casing height above land surface 12 in., weight 2.35 lbs./ft.			in. to 35 ft., weight 2.35 lbs./ft.		in. to 35 ft., weight 2.35 lbs./ft.		in. to 35 ft., weight 2.35 lbs./ft.		in. to 35 ft., weight 2.35 lbs./ft.	
TYPE OF SCREEN OR PERFORATION MATERIAL:										
1 Steel			3 Stainless Steel		5 Fiberglass		8 RMP (SR)		11 other (specify)	
2 Brass			4 Galvanized steel		6 Concrete tile		9 ABS		12 None used (open hole)	
SCREEN OR PERFORATION OPENING ARE:										
1 Continuous slot			3 Mill slot		5 Gauzed wrapped		8 Saw cut		11 None (open hole)	
2 Louvered shutter			4 Key punched		6 Wire wrapped		9 Drilled holes			
					7 Torch cut		10 Other (specify)			
SCREEN-PERFORATION INTERVALS:										
from 35			ft. to 55		ft., From		ft. to		ft.	
from			ft. to		ft., From		ft. to		ft.	
GRAVEL PACK INTERVALS:										
from 24			ft. to 55		ft., From		ft. to		ft.	
from			ft. to		ft., From		ft. to		ft.	
6 GROUT MATERIAL:										
1 Neat cement			2 Cement grout		3 Bentonite		4 Other			
Grout Intervals: From 4 ft. to 24			ft. From		ft. to		ft. From		ft. to	
What is the nearest source of possible contamination:										
1 Septic tank			4 Lateral lines		7 Pit privy		10 Livestock pens		14 Abandon water well	
2 Sewer lines			5 Cess pool		8 Sewage lagoon		11 Fuel storage		15 Oil well/Gas well	
3 Watertight sewer lines			6 Seepage pit		9 Feedyard		12 Fertilizer storage		16 Other (specify below)	
Direction from well? West How many feet? 15										
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) <u>reconstructed</u> , or (3) <u>plugged</u> under my jurisdiction and was completed on (mo/day/year) 11/07/1995 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 11/09/95 Under the business name of Harp Well & Pump Service, Inc. by (signature) <i>Jane Frederick</i>										