


1 LOCATION OF WATER WELL: County: Sedgwick		Fraction SW 1/4 NW 1/4 NW 1/4	Section Number 25	Township Number T 27 S	Range Number R 1 EW																																																
Distance and direction from nearest town or city street address of well if located within city? 400 S. West Street, Wichita, Ks																																																					
2 WATER WELL OWNER: RR#, St. Address, Box # Coatal Mart #9109 Attn: Denie Konen City, State, ZIP Code 110 S. Main, Suite 500, Wichita, Ks 67202 Board of Agriculture, Division of Water Resources Application Number: -----																																																					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL 20 ft. ELEVATION: ----- Depth(s) Groundwater Encountered 1. 15.2 ft. 2. ----- ft. 3. ----- ft. WELL'S STATIC WATER LEVEL 13.64 ft. below land surface measured on mo/day/yr 1/9/96 Pump test data: Well water was ----- ft. after ----- hours pumping ----- gpm Est. Yield ----- gpm; Well water was ----- ft. after ----- hours pumping ----- gpm Bore Hole Diameter 8.625 in. to 20 ft. and ----- in. to ----- ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well mw-2 Was a chemical/bacteriological sample submitted to Department? Yes ----- No X ; If yes, mo/day/yr sample was submitted ----- Water Well Disinfected? Yes ----- No X																																																			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ----- Clamped ----- 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded ----- 7 Fiberglass ----- Threaded X Blank casing diameter 2 in. to 10 ft. Dia. ----- in. to ----- ft. Dia. ----- in. to ----- ft. Casing height above land surface 0 in. weight SCH 40 PVC lbs./ft. Wall thickness or gauge No. ----- TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) ----- 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) ----- SCREEN-PERFORATED INTERVALS: From 10 ft. to 20 ft. From ----- ft. to ----- ft. SAND From ----- ft. to ----- ft. From ----- ft. to ----- ft. GRAVEL PACK INTERVALS: From 9 ft. to 20 ft. From ----- ft. to ----- ft. From ----- ft. to ----- ft. From ----- ft. to ----- ft.																																																					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other ----- Grout Intervals: From 0 ft. to 7 ft. From 3 ft. to 9 ft. From ----- ft. to ----- ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Contaminated Si 13 Insecticide storage Direction from well? ----- How many feet? -----																																																					
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>GL</td> <td>0.50</td> <td>Concrete</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.50</td> <td>3.00</td> <td>Fill sands, silts, clays</td> <td></td> <td></td> <td></td> </tr> <tr> <td>3.00</td> <td>7.50</td> <td>Silty Clay</td> <td></td> <td></td> <td></td> </tr> <tr> <td>7.50</td> <td>13.50</td> <td>Sandy Silt</td> <td></td> <td></td> <td></td> </tr> <tr> <td>13.50</td> <td>20.00</td> <td>Sand (SP)</td> <td></td> <td></td> <td></td> </tr> <tr> <td>20.00</td> <td>TD</td> <td>End of Borehole</td> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="6" style="height: 100px; vertical-align: bottom; text-align: right;"> Flush Mount waiver D. Taylor 7/14/95 </td> </tr> </tbody> </table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	GL	0.50	Concrete				0.50	3.00	Fill sands, silts, clays				3.00	7.50	Silty Clay				7.50	13.50	Sandy Silt				13.50	20.00	Sand (SP)				20.00	TD	End of Borehole				Flush Mount waiver D. Taylor 7/14/95					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																
GL	0.50	Concrete																																																			
0.50	3.00	Fill sands, silts, clays																																																			
3.00	7.50	Silty Clay																																																			
7.50	13.50	Sandy Silt																																																			
13.50	20.00	Sand (SP)																																																			
20.00	TD	End of Borehole																																																			
Flush Mount waiver D. Taylor 7/14/95																																																					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/21/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 585 This Water Well Record was completed on (mo/day/yr) 1/15/95 under the business name of Associated Environmental, Inc. by (signature) [Signature]																																																					