

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		<u>NE 1/4 NW 1/4 NE 1/4</u>	<u>20</u>	T <u>27</u> S	R <u>1</u> E <u>W</u>
Distance and direction from nearest town or city street address of well if located within city? <u>9203 W. Central, Wichita, KS.</u>					
2 WATER WELL OWNER: <u>Wenger Oil Co./ Marvin Wenger</u>					
RR#, St. Address, Box # : <u>2701 Anderson</u>				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code : <u>Newton, Ks. 67114</u>				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>26'6"</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>20'</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>20.28</u> ft. below land surface measured on mo/day/yr <u>4-28-96</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>8 1/2"</u> in. to <u>26'6"</u> ft., and in. to ft.			
WELL WATER TO BE USED AS:					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u> X If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes <u>No</u> X					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 <u>PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded <u>X</u>					
Blank casing diameter <u>2.375</u> in. to <u>16'</u> ft., Dia. in. to SDR <u>13</u> ft.					
Casing height above land surface <u>Flush Mt.</u> in., weight lbs./ft. Wall thickness or gauge No. <u>SCH. 40</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 <u>Mill slot</u> 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
SCREEN-PERFORATED INTERVALS: From <u>26'</u> ft. to <u>16'</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>26'6"</u> ft. to <u>14'</u> ft., From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement 2 <u>Cement grout</u> 3 <u>Bentonite</u> 4 Other Grout Intervals: From <u>14'</u> ft. to <u>4'</u> ft., From <u>4'</u> ft. to <u>0'</u> ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 <u>Fuel storage</u> <u>Fourer</u> 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? <u>In Old Tank Pit</u> How many feet? <u>0'</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.50	Asphalt			
.50	8.50	Fine-coarse grained sand-sand fill, dry, no odor.			
8.50	14.75	Med brn sandy clay w/ green clay mottling, mod. odor, soft, moist, dk gray sandy clay banding at 15'.			
14.75	26'6"	Gray sand & gravel w/ some silt, fine-very coarse grain sand, moist to wet at 20', strong odor.			
<u>E.H. OK'd by Don Taylor</u>					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>4-22-96</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>539</u> This Water Well Record was completed on (mo/day/yr) <u>5-18-96</u> under the business name of <u>JB Environmental Drilling</u> by (signature) <u>James Becker</u>					